

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2024/ 449

Dated :. J.4././/./2024

FIRE SAFETY CERTIFICATE

Certified that the Dada International Guest House located at 3339-3968-71, Kaseruwalan, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors Ground floor (04 guest room + reception), 1st floor to 3rd floor (08 guest rooms at each floor) 4th floor not in use as per affidavit dated 29.01.2020 total 28 guest rooms up to third floor only, owned occupied by Dada International Guest House was earlier granted FSC by this department vide letter no.F6/DFS/MS/GH/NDZ/2021/548 dated 29/12/21. Now, the premises was re-inspected by the officers concerned of this department on 04/11/24 in the presence of Sh. Gopal and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (04 guest room + reception), 1st floor to 3rd floor (08 guest rooms at each floor) total 28 guest rooms up to third floor only, and valid up to the period of three year from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Copy to:-

1. The Commissioner, North Delhi Municipal Corporation, Civic Centre, New Delhi: to ensure the occupancy as detailed above and deviation if any.

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi online id no.2024101715804 dated 17/10/24.

3. The Manager, Dada International Guest House, 3339-3968-71, Kaseruwalan, Pahar Ganj, New Delhi.

Conditions for the validity of Fire Safety Certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house up to third floor only.

2. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape such as staircase, exits, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry". 9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT 1. Name & address of the building:-Dada International Guest House located at 3339-3968-71, Kaseruwalan, Pahar Ganj, New Delhi 2. Type of occupancy:-Residential, Sub Division-A-1 Gr. + 04 Upper floors (total 28 Guest rooms) Ground floor (04 guest room + reception), 1st floor 3rd floor (08 guest rooms at each floor) and 4th floor having given an affidavit dated 29.01.2020 regarding not to use any floor above third floor 3. Type of case:-Renewal 4. Details of previous FSC:-No. F6/DFS/MS/GH/NDZ/2021/548 dated 29/12/21 Fire safety directives No.-N/A 6. Date of inspection:-04/11/24. 7. Name of the inspecting officer:-Sh. Ravinder Singh(ADO/CC) 8. Name & designation of officer From the building side:-Sh. Gopal 9. Year of construction:-10. Applicant's letter No:-Online id no.2024101715804 dated 17/10/24. Old Case Minimum Standards on fire S.No. Requirement Provided at site Remarks Æxisting fire Prevention and fire safety MR/NMR safety U/R 33 arrangements 1. Access to Building 1) Road width 06 mtr. 06 mtr. MR 2) Gate width N/A N/A N/A 3)Width of internal road N/A N/A N/A Number, Width Type & Arrangement of Exits 2. A. Number of staircases 1. Upper floors 01 Nos. 01 Nos. MR 2. Basements N/A N/A N/A B. Width of staircase 1. Upper floors 1.25 mtr. 1.25 mtr. -MR 2. Basements N/A N/A N/A C. Protection of exits 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A 01 D. No. of continuous 01 MR staircase to terrace E. Width of corridor N/A N/A N/A MR 1 mtr. 1 mtr. F. Door size Compartmentation 3. 1) Fire check door N/A N/A N/A N/A N/A 2) Sealing of electrical shafts N/A 3) Fire rating of shaft door N/A N/A N/A N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers Smoke Management System 4. N/A N/A N/A 1) Basements Natural/exhaust MR 2) Upper floors 12 a/c per fan hour

	, ,	
13		

	•			7
	Fire Extinguishers		10 Nos.	MR
5.	1) Total numbers	10 Nos.	10 Nos.	MR
		ABC & CO2	ABC & CO2	MR
	2) Types	Required	Provided	IVIK
	3) ISI marking			MR
6	First-Aid Hose Reel	01	01	IVIK
	1) Total number of each			MR
	floor	30 mtr.	30 mtr.	The state of the s
	2) Length of hose reel hose	05 mm	05 mm	MR
	3) Nozzle diameter	Alarming Syste	Ten	
7.	Automatic Fire Detection & Alarming System 1) Type of detectors CO Required Provided			MR
	1) Type of detectors CO	Roquiis		
	Type	Ground floor	Provided	MR
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	Required	Provided	MR
	4) Alternate source of power	Ground floor	Provided	MR
	5) Hooter's Location	CARRY CANALANT MA	Provided	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Flovided	
10.	Automatic Sprinkler System	ISMA	N/A	N/A
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	IVA	
	ceiling			
11.	Internal Hydrants	I NI/A	N/A	N/A
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	IVI	
	floor	N/A	N/A	N/A
	3) Hose box	IVA	A.W. A.B.	
12.	Yard Hydrants	N/A	N/A	N/A
	1) Total number of hydrants	1040 V.Vijenti	N/A	N/A
	2) Hose box	N/A	IVA	
13.	Pumping Arrangement	NI/A	N/A	N/A
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	IN/EX	ALMATERS.
	pump	N/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main	IVA	*****	
	pump	N/A	N/A	N/A
	d) Jockey pump out put e) Jockey pump head	N/A	N/A	N/A
			N/A	N/A
		N/A	N/A	N/A
	g) Stand by pump head h) Auto starting/Manual	N/A	N/A	N/A
	stopping		A-1 M - TABLE	The Carrotters
	2) Terrace level			
		225 LPM	225 LPM /	MR
	a) Discharge of pump b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump		Provided	MR
	ar Auto starting or pump	1787 1887 1888 1888 1888 1888	TO A STATE OF THE POSITION	11

N/23

4.	Captive Water Storage for Fire Fighting					
	i) Olider ground tank	N/A	N			
	capacity		N/A	N/A		
	a) Draw-off connection	N/A	N/A	NU		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	N/A	N/A	N/A		
	d) Over head tank capacity	2500 ltr.	2500 ltr.	N/A MR		
15.	Exit Signage.	Required	Provided			
16. Pro	Provision of Lifts.	required	Flovided	MR		
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	 b) Pressurization of lift lobby 	N/A	N/A	N/A		
	c) Communication in lift car	Required	Provided	MR		
	d) Fireman's switch	Required	Provided	M		
	e) Lift signage	Required	Provided	MR		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	MR N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	27/1		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
	20 370 385	DAMES.	INA	N/A		
	e) Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection System if any:	n for Protection	on of special Risk,	NA		

The above fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter No. F6/DFS/MS/GH/NDZ/2021/548 dated 29/12/21, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, DFA is prepared and put up for kind perusal/approval please.

Signature of the Inspecting Officer

Name: - Ravinder Singh

Designation: - ADO (CC)

(i)

7/11/24

Aycho (aroz)

111 11 20

Director Mill n

mye