

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No. F6/DFS/MS/GH/NDZ/2024/ 459

Dated: 18 / 11 /2024

FIRE SAFETY CERTIFICATE

Delhi Fire Service Tel: 011-23414000

Copy to:-

- 1. The Commissioner, MCD:- to kindly ensure the occupancy as detailed above & deviation, if any.
- The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2024102516119 dated 25.10.2024.
- 3. The Licensee, M/s Hotel New City Palace at 726, Motor Market, Jama Masjid, Delhi 06. Conditions for the validity of fire safety certificate
- This FSC is valid for 2nd floor only.
- 2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi
 Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before
 occupancy of the same.
- 10. The occupancy above 2nd floor are not allowed as per clause 7.31 in UBBL-2016.

	1.	Name and address of the buildin	g: M/s Hotel New	City Palace o	726 Mate	
-	2			Masjid, Delbi	- 06.	
	2.	2. Type of occupancy with details of Residential Sub Division-A-				
		floors:	(Ground + Me		nner floors	
	- 1		Ground floor -	(commercial u	se)	
	- 1		Mezzanine - (co	mmercial use)		
	- 1		1" floor - (Post	office + staff r	oom)	
			2"" floor - (1) g	uest rooms + r	eception +	
			office),	office),		
			ace - (not in us	e as per		
	3.	Type of case:	affidavit dated 1 RENEWAL (old			
7	4.	Details of previous FSC:	(NDZ/2018/93	1 Janear		
		5	NDZ/2018/93	a dated		
	5.	Fire safety directives no.:	07.05.2018 NA			
	6.	Date of inspection:	08.11.2024			
_	7.	Name of the inspecting officer: Sumit Kumar, ADO (SPM)				
	8. 1	Name and designation of the office	er	, , , , , ,		
_	_ 1	rom the building side:	Manager			
	9.	Year of construction:	1991			
8	10 I	Reference letter no.:	Online application	n ID No. 2024	102516119	
	\perp		dated 25.10.2024			
S,N	200	Minimum standard of Fire	Requirements	Provide at	Remark	
	1	Prevention and Fire Safety U/R 33	(Existing Fire &	site	S	
			Safety Measures)	(PSS)	MR/N	
1	+			100	MR	
_		Access to Building	T	177	120	
	E	- I Tomb Milani	NA .	12 m	NA	
		E LIBENIAN SANDERS	NA	NA	NA	
	0	1010 AVERTONIA (TELEVISIONE PARENTA)	NA	NA	NA	
		lumber, Width, Type & Arrangen	nent of Exits			
	A	No. Of Staircase:		(9)		
		a) Upper Floor	01 no.	01 no.	MR	
	1	b) Basements	NA	NA	NA	
	В	Width of the Staircase:	W.			
		Constitution of the Consti				
		a) Upper floors	0.80 m	0.98 m	MR	
		b) Basements	NA	NA	NA	
	C	Protection of Exits				
	1	a) Fire Check Door	NA	NA	NA	
	1	b) Pressurization	NA	NA	NA	
	-	No. Of continuous staircase to	01	21		
	D		01	01	MR	
		terrace:				
	F	Width of the corridor	NA	NA	NA	
	P	Door size	0.80 mtr.	0.80 mtr.	MD	
	E	R. C.	0.00 mu.	0.80 mtr.	MR	
3		mpartmentation:	Tata .			
	Α	Fire Check doors	NA NA	NA	NA	
	l	Sealing of Electrical Shafts	NA	NA	NA	
	n		1 2 1			
	В		NA	NA	I NIA	
		Fire rating of shaft	NA	NA	NA	
	С	Fire rating of shaft Doors	70.5 44.5.1	.48212		
		Fire rating of shaft Doors Water curtain	NA	NA	NA	
	С	Fire rating of shaft Doors	70.5 44.5.1	.48212		
4	C D	Fire rating of shaft Doors Water curtain Fire dampers	NA	NA	NA	
4	C D	Fire rating of shaft Doors Water curtain Fire dampers oke management System:	NA NA	NA	NA	
4	C D	Fire rating of shaft Doors Water curtain Fire dampers	NA NA	NA NA	NA NA	
	C D Sm A B	Fire rating of shaft Doors Water curtain Fire dampers oke management System: Upper floors Basements	NA NA	NA NA	NA NA	
4	C D Sm A B	Fire rating of shaft Doors Water curtain Fire dampers oke management System: Upper floors Basements e extinguishers	NA NA 12 ACPH NA	NA NA NA	NA NA NA NA	
	C D Sm A B Fire	Fire rating of shaft Doors Water curtain Fire dampers oke management System: Upper floors Basements e extinguishers Total numbers	NA NA 12 ACPH NA 08 nos.	NA NA NA NA O8 nos.	NA NA NA NA MR	
	C D Sm A B	Fire rating of shaft Doors Water curtain Fire dampers oke management System: Upper floors Basements e extinguishers Total numbers	NA NA 12 ACPH NA 08 nos. CO2 , ABC	NA NA NA NA O8 nos. CO2, ABC	NA NA NA NA	
	C D Sm A B Fire	Fire rating of shaft Doors Water curtain Fire dampers oke management System: Upper floors Basements e extinguishers Total numbers	NA NA 12 ACPH NA 08 nos.	NA NA NA NA O8 nos.	NA NA NA NA MR	

	A	Aid Hose reel Total no. at 2 nd floor	01 no.	01 no.	MR		
	В	Length of Hose Reel	30 m	30 m	MR		
	C	Nozzle diameter	05 mm	05 mm	MR		
7		natic Fire Detection and Alarm System					
	A	Type of Detectors (CO type)	Required	Provided	MR		
	В	Location of main Panel	Required	At 2 nd floor	MR		
	C	Location of Repeater Panel	NA	NA	NA		
	D	Alternate power Source	Required	Provided	MR		
	E	Hooter's location	Required	Provided	MR		
8	MOE	FA	Required	Provided	MR		
9	Public Address System		Required	Provided	MR		
10					-		
	A	Basement	NA	NA	NA		
	В	Upper Floor	NA	NA	NA		
	C	Sprinklers above false ceiling	NA	NA	NA		
11	Intern	nal Hydrants	73. 74.				
	A	Size of the riser/down comer	NA	NA	NA		
	В	No. Of hydrants per floor	NA	NA	NA		
	C	Hose box	NA	NA	NA		
12	Yard	Hydrants			-		
	Α	Total no. of hydrants	NA	NA	NA		
	В	Hose box	NA ·	NA	NA		
13	Pump	ing arrangements					
	A	Ground Level					
	-5,-	a) Discharge of main pump	NA	NA	NA		
		b) Head of main pump	NA	NA	NA		
		c) Number of main pump	NA	NA	NA		
		d) Discharge of jockey pump	NA	NA	NA		
		e) Head of jockey pump	NA	NA	NA		
		f) Discharge of Standby pump	NA	NA	NA		
		g) Head of Standby pump	NA	NA	NA		
		h) Auto starting/ manual stopping	NA	NA	NA		
	В	Terrace Level			*		
		a) Discharge of terrace pump	240 LPM	240 LPM	MR		
		b) Head of terrace pump	35 m	35 m	MR		
		c) Alternate power supply	Required	Provided	MR		
		d) Auto starting of pump	Required	Provided	MR		
14	Centiv	e Water Storage for Fire Fighting		Latination (Cont.)			
14	A	Underground tank capacity	NA	NA	NA		
	В	Draw off connection	NA	NA	NA		
	C	Fire Service Inlet	NA	NA	NA		
8	E	Access to tank	NA	NA /	NA		
	D	Overhead tank capacity	2500 ltrs.	2500 ltr	MR		
5			Required	Provided			
_	Exit Signage Required Provided MR Provision of lift						
16	-	Pressurization of lift shaft	NA	NA	NI.		
	A		NA NA		NA		
	В	Pressurization of lift lobby	THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TW	NA	NA		
-	С	Communication in lift car	NA	NA	NA		
1	D	Fireman switch	NA	NA	NA		
_	Е	Lift signage	NA	NA	NA		
7	Standb	y Power Supply	Required	Provided (DG set 4 KVA)	MF		

18	Refuge Area					
	Α	location	NA	NA	NA	
	В	Total area	NA	NA	NA	
19						
	Α	Fire Detection System panel	NA	NA	NA	
	В	Flow switch panel	NA	NA	NA	
	C	P A system panel	NA	NA	NA	
	D	Battery backup	NA	NA	NA	
	E	Building floor plan	NA	NA	NA	
20	Special Fire Protection for special risk if any					

The fire protection systems provided in the building were tested, checked at randomly and found functional at the time of inspection.

Shortcomings communicated vide letter No.F6/DFS/MS/GH/NDZ/2024/595 dated 19/09/2024 has been rectified.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No F6/DFS/MS/GH/NDZ/2018/934 dated 07.05.2018 is recommended to be renewed 2nd floor only, under Rule 35 of the Delhi Fire Service Rules 2010.

> Signature of the Inspecting Officer Sumit Kumar Name ADO (SPM) Designation

for Signature, Please.

Director (DAS