e-112

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2024/ 453

Dated :. 1.4.1.11.12024

FIRE SAFETY CERTIFICATE

Certified that the Krishna Guest House located at 45, Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (06 guest rooms + reception + lobby + 01 office), 1st floor to 3rd floor (10 guest rooms at each floor), 4th & 5th floor not in use as per affidavit dated 05.12.2019 total 36 guest rooms up to third floor only owned/occupied by Krishna Guest House, was earlier granted FSC by this department vide No.F6/DFS/MS/GH/NDZ/2021/356 dated 03/09/21. Now, the premise was re-inspected by the officers concerned of this department on 08/11/24 in the presence of Manager and guest house premises has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the guest house premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (06 guest rooms + reception + lobby + 01 office), 1st floor to 3rd floor (10 guest rooms at each floor), total 36 guest rooms up to third floor only and valid up to the period of three year from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 14 /11/2029 at New Delhi by.

Atul Garg) BIRECTOR Ihi Fire Service

Copy to:-

- The Commissioner, North MCD, Civic Centre, New Delhi.: to ensure that not to use any floor above third floor and to verify the addition/alteration in the building.
- The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref.ID 2024050807171 dated 17/10/24.
- 3. The Manager, Krishna Guest House at 45, Arakashan Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house up to third floor only.
- Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape such as staircase, exits, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J'
 [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- Any flammable material for interior decoration is prohibited.

INSPECTION REPORT

1. Name & address of the building Krishna Guest House at 45, Arakashan

Road, Pahar Ganj, New Delhi. Residential, Sub Division-A-1

Gr. + 05th Upper floors (total 36 Guest rooms) Ground floor (06 guest rooms + reception + lobby + 01 office), 1st floor to 3rd floor (10 guest rooms at each floor), 4th & 5th floor not in use as per affidavit

dated 05.12.2019 submitted by owner.

Type of case:-

4. Details of previous FSC:-No F6/DFS/MS/GH/NDZ/2021/356 dated

03/09/21.

Fire safety directives No.-

N/A

6. Date of inspection:-

Type of occupancy:-

08/11/24.

7. Name of the inspecting officer:-

Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer

From the building side:-

Manager

9. Year of construction:-

2007

| 10. | Applicant's letter No:- | ID 2024050807 | 171 dated 17/10/24. | Old Case |
|-------|---|--|--|-------------------|
| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement/ Existing fire safety arrangements | Provided at site | Remarks MR/NMR |
| 1. | Access to Building | | | |
| | 1) Road width | N/A | 06 mtr. | MR |
| | 2) Gate width | N/A | N/A | N/A |
| | 3)Width of internal road | N/A | N/A | N/A |
| 2. | Number, Width Type & Arr | angement of Ex | its | |
| ۷. | A. Number of staircases | | | |
| | 1. Upper floors | 01 Nos. | 01 Nos. | MR |
| | 2. Basements | N/A | N/A | N/A |
| | B. Width of staircase | | | \ m |
| | 1. Upper floors | 1.25 mtr. | provided | MR |
| | 2. Basements | N/A | N/A | N/A |
| | C. Protection of exits | | | MD |
| | 1. Fire check door | Required | Provided | MR N/A |
| | 2. Pressurization | N/A | N/A | N/A |
| | D. No. of continuous staircase to terrace | N/A | N/A | |
| | E. Width of corridor | N/A | N/A | N/A |
| | F. Door size | 1.0 mtr. | 1.0 mtr. | MR |
| | Compartmentation | | | |
| 3. | Compartmentation | N/A | N/A | N/A |
| | Fire check door Sealing of electrical shafts | | N/A | N/A |
| | 2) Sealing of electrical shares | N/A | N/A | N/A |
| | 3) Fire rating of shaft door | N/A | N/A | N/A |
| | 4) Water curtain | N/A | N/A | N/A |
| | 5) Fire Dampers Nongement System | | | 15776 |
| 4. | Smoke Management System | N/A | N/A | N/A |
| | Basements Upper floors | 12 ACPH | Natural Ventilation/exh aust fan | MR |
| | Fire Extinguishers | | | MR |
| 5. | 1) Total numbers | 10 Nos. | 16 Nos. | MR |
| | 2) Types | ABC & CO2 | ABC & CO2 | IVIIC |

N139

| | NI39 | | | |
|------------|-------------------------------|-----------------|----------|------|
| 6. | 3) ISI marking | Required | Provided | MR_ |
| 0. | First-Aid Hose Paul | Required | Flovided | |
| | 1) Total number of each floor | 01 | 01 | MR |
| | Length of hose real hose | 30 mtr. | 30 mtr. | MR |
| 7. | 3) Nozzle diameter | 05 | 06 | MR |
| <i>'</i> • | Automatic Fire Detection & | Alarming Sys | tem | |
| | | Required | Provided | MR |
| | Type | | Tiovided | |
| | 2) Location of main panel | Gr. floor | Provided | MR |
| | Di Location of repeater panel | Required | Provided | MR |
| | T) Alternate source of norman | Required | Provided | MR |
| | 3) Hooter's Location | Gr. floor | Provided | MR |
| 8. | MOEFA | Required | | MR |
| 9. | Public Address System | Danii i | Provided | |
| 10. | Automatic Sprinkler System | Required | Provided | MR |
| | 1) Dasement | | | |
| | 2) Upper floors | N/A | N/A | N/A |
| | 3) Sprinkler above false | N/A | N/A | N/A |
| | ceiling | N/A | N/A | N/A |
| 11. | Internal Hydrants | | | |
| | 1) Size of riser/down-comer | 100 | | |
| | 2) Number of hydrants per | 100 mm | 100 mm | MR |
| | floor | 01 | 01 | MR |
| | 3) Hose box | | | |
| 12. | Yard Hydrants | 01 | 01 | MR |
| | 1) Total number of hydrants | | | |
| | 2) Hose box | N/A | N/A | N/A |
| 3. | Pumping | N/A | N/A | N/A |
| | Pumping Arrangement | | | IVA |
| | 1) Ground level | N/A | N/A | 27/1 |
| | a) Discharge of main | N/A | N/A | N/A |
| | pump | A A TONING TO A | IVA | N/A |
| | b) Head of main pump | N/A - | N/A | |
| | c) Number of main | N/A | | N/A |
| | pump | 1011 | N/A | N/A |
| | d) Jockey pump out put | N/A | | |
| | e) Jockey pump head | N/A | N/A | N/A |
| | f) Stand by pump output | | N/A | N/A |
| | g) Stand by pump head | N/A | N/A | N/A |
| | h) Auto starting/Manual | N/A | N/A | N/A |
| | stopping | N/A | N/A | |
| | i) | | | N/A |
| | 2) Terrace level | | | |
| | -/ Telface level | | | |
| | a) Discharge of pump | 450 | | / |
| | b) Head of pump | 450 LPM | provided | 1 |
| | or build | 30 mtr. | provided | MR |
| | | Required | | MR |
| | d) Auto starting of pump | Required | Provided | MR |
| | ioni 🍮 | 1500 | Provided | MR |
| _ | 0 | | | |
| 1. | Captive Water Storage for F | ino Et al | | |
| | 1) Under ground tank | ne Fighting | | |
| | capacity | N/A | N/A | |
| | | 1 | | N/A |

| | a) Draw-off connection | N/A | N/A | N/A |
|-----|--|------------|------------|-----|
| | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank capacity | 5,000 ltr. | provided | MR |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided / | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System for Protection of special Risk, if any: | | | N/A |

The above fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter No. F6/DFS/MS/GH/NDZ/2021/356 dated 03/09/21, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, DFA is prepared and put up for kind perusal/approval please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

11/11/24

Mcco (wos

Riv P

Dinester 13/11/20

AOUG