Dated: 18./11./2024



No.F6/DFS/MS/GH/2024/ 458

FIRE SAFETY CERTIFICATE

Certified that the Twenty Twenty Guest House, located at 3972-76, Kaseruwalan, Paharganj, New Delhi. comprised of Ground+3 Upper floors, ground floor reception + office + lobby + 02 guest rooms, (1st to 3rd floor 06 guest rooms at each floor) 4th floor not to use as per affidavit dated 16.01.2020,total 20 guest rooms only was earlier granted by this department vide letter No. F6/DFS/MS/GH/2021/146 dated 18/03/21. Now, The premise was re-inspected by the officer concerned of this department on 12/11/24 in the presence of Sh. Puran chand and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Group A-1 ground floor reception + office + lobby + 02 guest rooms, 1st to 3rd floor 06 guest rooms at each floor total 20 guest rooms only and valid up to the period of three year from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 18/11/2024. at New Delhi by.

DIRECTOR Delhi Fire Service

Copy to:-

- The Commissioner, North MCD, Civic Centre, New Delhi.: to ensure that not to use any floor above third floor and to verify the addition/alteration in the building.
- The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref.ID 2024102616138 dated 26/10/24.
- The Manager, M/S Twenty Twenty Guest House, located at 3972-76, Kaseruwalan, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house up to third floor only.
- Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- The compliance with regards to electrical installation, structural stability, set back area, occupancy
 and any deviation in construction etc. shall be verified from authority concerned.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape such as staircase, exits, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT

Name & address of the building

Twenty Twenty Guest House, located at 3972-76, Kaseruwalan, Pahar Ganj, New

Delhi.

Type of occupancy: -

Residential Group, Ground+4 upper Floor (20 guest rooms) ground floor

reception + office + lobby +02 guest rooms, 1" floor to 3rd floor 06 guest rooms at each floor & 4th floor (terrace floor -82 guest rooms + pantry & staff room not in use as per

affidavit dated 16.01.2020)

Type of case: -

Details of previous FSC: -

Renewal

No.F6/DFS/MS/GH/2021/146 dated

Sh. Ravinder Singh, ADO (CC)

18.03.2021.

Fire safety directives No.-

Date of inspection: -

N/A

12/11/24.

7. Name of the inspecting officer:-

Name & designation of officer

From the building side:-Year of construction:- Sh. Puran chand

2011

10. Applicant's letter No:-

ID No. 2024102616158 dated 26/10/24

Old Case S.No. Minimum Standards on fire Requirement/ Provided at site Remarks Prevention and fire safety U/R 33 Existing fire MR/NMR safety arrangements 1. Access to Building Road width N/A N/A N/A 2) Gate width NA N/A N/A 3)Width of internal road N/A N/A N/A 2. Number, Width Type & Arrangement of Exits A. Number of staircases Upper floors 01 No. 01 No. MR. 2. Basements N/A N/A N/A B. Width of staircase Upper floors 80cm. 125 cms MR 2. Basements N/A N/A N/A C. Protection of exits 1. Fire check door N/A N/A N/A N/A 2. Pressurization N/A N/A D. No. of continuous N/A N/A N/A staircase to terrace E. Width of corridor N/A N/A N/A NA F. Door size N/A N/A Compartmentation N/A 3. N/A 1) Fire check door N/A N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A Smoke Management System 4. N/A N/A 1) Basements N/A Required Provided 2) Upper floors MR Fire Extinguishers 5. 1) Total numbers 12 Nos. 12 Nos. MR ABC & CO2 ABC & CO2 2) Types MR

Nho

		NIM		
	La vár	Required	Provided	MR
	3) ISI marking	7.04		
6.	First-Aid Hose Reel	01	01	MR
	1) Total number of eachfloor	30 mtr.	30 mtr.	MR
	2) Length of hose reel hose	05 mm	05 mm	MR
	3) Nozzle diameter	Alerming Sy	stem	
7.	Automatic Fire Detection &	Required	Provided	MR
	1) Type of detectors CO	Required		
	Туре	Gr. floor	Provided	MR
	2) Location of main panel		Provided	MR
	3) Location of repeater panel	Required	Provided	MR
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Gr. floor		MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MIK
10.	Automatic Sprinkler System			NI/A
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling			
11.	Internal Hydrants			
11.	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor			7
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			j.
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
12	Pumping Arrangement			
13.	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump	1,472		
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main	N/A	N/A	N/A
	pump	1,7,2	- "	1000
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump	N/A	N/A	N/A
	output			
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping			IV/A
	2) Terrace level			
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	
	c) Power supply	Required	Provided Provided	MR
	d) Auto starting of	Required	Provided	MR
	pump	Required	Trovided	MR
	F			
14.	Captive Water Storage for I	1		
	1) Under ground tank	N/A	N/A	
	capacity	11/21	IVA	N/A
	a) Draw-off connection	N/A	N/A	
	b) Fire service inlet	N/A	N/A N/A	N/A
	, and so the milet	14/71	I IV/A	N/A

	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	Pressurization of lift shaft.	N/A	N/A	N/A
	 b) Pressurization of lift lobby 	N/A	N/A	N/A
	 c) Communication in lift car 	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Systif any: ABC & CO ₂ .	stem for Prote	ction of special Risk,	N/A

The above fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter No. F6/DFS/MS/GH/2021/146 dated 18/03/21, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, DFA is prepared and put up for kind perusal/approval please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

13/11/24 Dyces (mg)

Riv 9

Directa / Maria

mala