



## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/Mixed/2024/SZ / 693

Dated: 26/11/2024

## FIRE SAFETY CERTIFICATE

Certified that the M/s National Trust For the Handicapped located at A-2, Saheed Jeet Singh Marg, Qutab Institutional Area, New Delhi-110067 comprised of Basement, Ground plus Four upper floors owned/occupied by National Trust For Handicapped was Safety Certificate by this department vide letter F6/DFS/MS/Mixed/Occupancy/2021/SZ/579 dated 23/11/2021. The premise was reinspected by the officer concerned of this department on 20/11/2024 in the presence of Mr. Naresh Sharma and observed that the premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that building is fit for occupancy Class - Mixed Occupancy (Educational/Business/Assembly)." with effect from 21/11/2024 for period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued  $\frac{26}{11}$  2024 at New Delhi by

DIRECTOR DELHI FIRE SERVICE

Copy to: -

1. National Trust for the Handicapped, at A-2, Saheed Jeet Singh Marg, Qutab Institutional Area, New Delhi-110067.

 The Executive Engineer (Bldg) HQ-II, Delhi Municipal Corporation, 9th Floor, Civic Centre, Minto Road, New Delhi 110002.

## Conditions for the validity of Fire Safety Certificate:-

- All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection.
- Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- Any Deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 4. The Basement shall be used as per the provisions of BBL/NBC Part-IV.
- The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL- 2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."
- This FSC is valid for old structure only except the portion additional floor fabricated in between ground and First floor of the building.

1			INSPEC	TION REPORT	7/-				
1			a Address of the Building	National Trust F	आज़ा or Handian 1 1 2 3 3 11	दी क			
1	Name & Address of the Building			National Trust For Handicapped, A-2, Saheed Jeet Singh Marg, Qutab Institutional Area, New Delhi-110067					
2	T	ype o	f Occupancy						
			g Comprised of	Educational/Business/Assembly).  Basement, Ground & 04 Upper Floors					
3		1000	COCP	Renewai					
5		etails	of Previous NOC	F6/DFS/MS/Mixed/Occupancy/2021/SZ/579 dated					
)				23/11/2021					
6	Fi	re Sa	fety Directives Letter No	F.6/DFS/MS/BP/2013/164 dated 02/7/2013 Basement, Ground + 5 Upper Floors 20-11-2024					
97.9									
7		- 1 (1 - 2 ) a .	Inspection Cake Inspecting Officers	ADO Sh. Rajesh Kumar					
8	Na Na	Name of the Inspecting Officers  Name & Designation of Officers  Name & Designation of Officers  Name & Designation of Officers							
. 9	fee	m the	building side	2015 Outdoor diary no 7151 dated 30/09/2024					
10	Ve	ar of	construction						
11	_		t a handle						
S. No	Mi	nimu	m standards on Fire Frevention	requirements	MR/NMR				
	and	d Fire	Safety U/R 33						
1	Ac	cess t	o Building. Road width	12 mtr	Provided	MR			
		•	Gate width	4.5 mtr	Provided Provided	MR MR			
			Cinternal road	6 mtr	Provided	MK			
_	Nim	mher	, width, type & arrangement of	exits.					
2	a)	Num	ber of Staircase		Provided as per				
			Upper floors.	3 Nos+ 01 Ram	P NBC -IV of 2005	MR			
				05 Nos + 01	Provided	MR			
	1 .	➤ Basement floor.		Ramp					
	b)	Widt	h of Staircase	3 Nos. of 2 m+	2.02 m, 2.29 m &	MR MR (old Case)			
	-	> U	pper floors	one Ramp of 1.8 m 03 nos. of 02 m, 02 nos.	2.04 m + 1.96 m				
			1.00		(Ramps/ Staircase)				
		11 -			2.02 m, 1.95 m, 1.55				
	١,	D.	Basement floor		m, 1.54m & 1.56m +				
	1 ,	► B		of 1.5 + Ramp	7.25 M				
				of 7.6 m					
	c) F	rotec	tion of exits	Required	Provided	MR			
		Fi	re check door	Required in two		25.54			
				staircase	Provided	MR			
	> Pre		essurization			MR			
	d) N	o of	continuous staircase to terrace	03 nos. + One	03 Nos.	(old case			
	SACRET SAT			Ramp	The second of	MR			
	e) V	Vidth	of corridor	1.5m	1.45m	(old case			
	f) Door size			Educational/Bu	7.51				
	f) D	oor s	ize	siness (Final	Provided	MR			
00				Exit): Îm	Flovided				
				Auditorium 2 m	16.144-11707				
3	Comp	artm	entation.			100			
	•	Fire	check door.	Required	Provided	MR			
	•.		ling of electrical shafts.	Required	Provided	MR			
	•		rating of shaft door.	02 hrs.	Provided	MR			
	•		ter curtain	Required	Provided	MR			
	•		dampers.	Required	Provided	MR			
1. S	Smok	e Mai	nagement system.						
	•	Bas	ement	30 ACPH	Provided	MR			
	•	Upp	per floors	12 ACPH	Natural Ventilation	MR			
i.		xting	uishers.		THE PARTY OF THE PARTY OF THE PARTY.				
	<b>●</b> 30		d numbers	Required	60 Nos. Provided	MR			
	•	Тур	es	ABC Co2 &	Constant design of the second				
are a		ISI	Marking	W.Co2	ABC, Co2 & W.Co2	MR			
	- 65	1.01	- MILLANDE	ISI marked	Provided	MR			

6.	First Aid Hose Reels.							
	Total numbers on each floor.      Length of hose-reel hose.	Basement, 3 <sup>nd</sup> floor & 4 <sup>th</sup> floor: 05 Nos. GF, 1 <sup>st</sup> Floor & 2 <sup>nd</sup> Floor: 04 Nos. 30 mtr 5 mm		Provided Provided Provided	MR MR			
- 1	Nozzle Diameter							
7	4 4 4 4							
/	Automatic fire detection & alarming system.	5 mm   Flovidea		Tioridea				
	<ul> <li>Type of detectors</li> </ul>	Smoke & Heat	F	rovided	MR			
- 1	<ul> <li>Location of Main Panel</li> </ul>	Required Gr -NA-		ound Floor	MR			
	<ul> <li>Location of Repeater Panel</li> </ul>			-NA-	-NA- MR MR MR			
	<ul> <li>Alternate source of power</li> </ul>			rovided				
	Hooter's location	Required	All Floor					
8.	MOEFA			Provided				
9,	Public Address System	Required Provided		Provided	MR			
10.	Automatic Sprinkler System			1	JII.			
	Basement	Required		Provided	MR			
	Upper floors	Required	1	Provided	MR			
_///	Sprinkler above false ceiling	-NA-		-NA-	-NA-			
11.	Internal Hydrants.			I	) (D			
	Size of Riser/Down-comer      Number of Hydrant per floor	Basement, 3 <sup>rd</sup> flo & 4 <sup>th</sup> floor: 05 N GF, 1 <sup>st</sup> Floor & 2 Floor: 04 Nos.	os. 2 <sup>nd</sup> Provided		MR MR			
	Hose box.	Basement, 3 <sup>rd</sup> floor & 4 <sup>th</sup> floor: 05 Nos. GF, 1 <sup>st</sup> Floor & 2 <sup>nd</sup> Floor:04 Nos.		Provided	MR			
12.	Yard Hydrants.							
	Total number of hydrants.	Required 08 No		los. Provided	MR			
	Hose box.	Required	08 Nos. Provided		MR			
13.	Pumping arrangements.			Water Ma				
	Ground Level			1				
	Discharge of main pump.	2850 LPM		2850 LPM	MR			
	> Head of main pump.	70m		70m	MR			
	Number of main pumps.	02 Nos		03Nos	MR			
	Jockey Pump output.	180 LPM & 280	LPM	Provided	MR			
	> Jockey Pump head.	70m 2850 LPM 70m		70m	MR			
	<ul> <li>Standby Pump output.</li> <li>Standby Pump head.</li> </ul>			2850 LPM	MR			
	N N=P++1P+2N 1. → N2 / 1975. N2 /			70m	MR			
	Pump house access.	Required		Provided	MR			
	347 - 510031 - 10000000000000000000000000000000	Required	-	Provided	MR			
	Terrace Level		Iv.					
	Discharge of pump.	-NA-		-NA-	-NA-			
	> Head of pump.	-NA-		-NA-	-NA-			
	<ul><li>Power supply.</li><li>Auto starting of pump.</li></ul>	-NA-		-NA-	-NA-			
		-NA-		-NA-	-NA-			
14.		1.00.000						
	Underground tank capacity.     Draw off connection	1,00,000 Ltr	11.4	Provided	MR			
	Plaw-off confection.	Required		Provided	MR			
	> Fire Service Inlet.	Required		Provided	MR			
	> Access to tank.	Required		Provided	MR			
	Overhead tank capacity.	20, 000 Ltr	Prov	ided of NBC-IV of 2005	MR			
15.	Exit Signage.	Required	_	Provided	and the second second			

Provision of Lifts. Pressurization of lift shaft Required Pressurization of lift lobby. Provided Required MR Communication in lift car. Provided Required MR Fireman's switch. Provided MR Lift signage. Required Provided MR Required Provided 17. Standby Power Supply MR Required Provided MR 18. Refuge Area Total area -NA--NA--NA-Location -NA--NA--NA-19. Fire Control Room. Detector system panel. Required Provided MR Flow switch panel. Required Provided MR Required PA system panel. Provided MR Required Battery backup. Provided MR Building floor plan. Required Provided MR Special Fire Protection System for the Segregation Provided 20. MR of Protection of special Risk, if any. HT/LT/Tran sformer etc.

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/Mixed/Occupancy/2021/SZ/579 dated 23/11/2021, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended for old building except the portion of additional floor fabricated in between ground and First floor of the building.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

eed Jeet Singh Marg, Qutab Institutional Area, New Delhi-11006 National Trust For