

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/SZ/2024/ 692

Dated: 26 /11 /2024

FIRE SAFETY CERTIFICATE

Certified that the building of Shri Ganinath CGHS Ltd. Located at Plot No-01, Sector-05, Dwarka, New Delhi - 110075, having 04 blocks comprised of Stilt + 07 upper floor/ Double stilt + 06 UFs was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/CGHS/2018/SZ/163, dated 24/01/2018. The premise was inspected by the officer concerned of this department on 04/11/2024 & 09/11/2024 in the presence of. Sh. Jia Ram (President)and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A-4 with effect from 26 11 2024 for a period of five years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .. 26 11 > 22 at New Delhi by.

(Atul Garg) Director

Delhi Fire Service

Copy to:

- The President, Shri Ganinath CGHS Ltd. Located at Plot No-01, Sector-05, Dwarka, New Delhi V. 110075.
- 2. The Joint Director (Building) DDA, Vikas Sadan, INA, Delhi-110023.

Condition for the validity of fire safety certificate:-

1. The staircase at terrace level shall be kept open & free from lock and key & all the exit shall be clear from any obstruction otherwise the FSC shall be null & void

 All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

4. The trained staff should be available round the clock.

- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

7. Basement if any shall be used as per building bye laws.

- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. www.dfs.delhigovt.nic.in.
- The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

 Name & address of the building: Shri Ganinath CGHS Ltd. Located at Plot No-01, Sector-05, Dwarka, New Delhi - 110075.

2. Type of Occupancy : Residential Building "A" (Apartment)

3. Type of Case : Renewal 04 blocks (Stilt + 07 upper floor/ Double stilt + 06 UFs)

4. Details of previous NOC : F6/DFS/MS/CGHS/2018/SZ/163, dated 24/01/2018

 Fire Safety directives Letter No.: F6//DFS/MS/96/CGHS/497, dated 12/04/1996 F6/DFS/MS/CGHS/BP/2011/971, dated 25/05/2011

6. Date of inspection

: 04/011/2024 & 09/11/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side : Sh. Jia Ram (President)

9. Year of Construction : 1996 & 2011

10. Applicant's letter No. : Email, dated-14/10/2024

| lo | Minimum standards on fire prevention and fire safety U/R 33 | As | Per N/3, | N/4 | & N/5 | Prov site | ided at | | Remarks MR/NMR | |
|----|--|--------------------------------------|--|-----|-------|--------------|--------------------|------|-------------------|--|
| | Access of building | 00 4wa | | Pro | vided | | N | 1R | | |
| | Road width | 9 mtrs Provided 4.5 mtrs Provided | | | | d | | MR | | |
| | • Gate width | 6 m | Provid | ed | | | M | IR C | old Case | |
| | Number, width, Type & Arrangen | nents of ex | cits | T | | | | | | |
| | a. Number of staircases • Upper floors • Basements b. Width of staircases • Upper floors | 1 no. each block Pr | | | | ovided | | | MR | |
| | | NA | - 1 A | | | | | | | |
| | | 1.25 m | 1.25 mtr 105 cm, 107cm, 111cm & 112cm | | | | MR(Being old case) | | | |
| | Basements | NA | 1 | A | | N/ | 1 | | | |
| | Protection of exits Fire check door | NI/A | N/A | | | | N/A N | | | |
| | | | N/A | | | | N/A | | N/A | |
| | Pressurization d. No of continuous staircase | | | | | Provided | | | MR | |
| | to terrace e. Width Of Corridor f. Door Size | N/A | | | | N/A | | | N/A | |
| | | 100 | 90 cm Prov | | | vided MR | | | | |
| 3. | Compartmentation | | | | | | | | | |
| ٥. | Fire check door | N/A | N/A | | | N/A | | N/A | | |
| | Sealing of electrical shaft | s Requi | Required | | | | Provided | | MR | |
| | Fire Rating of shaft door | N/A | N/A | | | | 1324 | | N/A | |
| | Water Curtain | N/A | N/A | | | | N/A | | N/A | |
| | Fire Dampers | N/A | N/A | | | | N/A | | N/A | |
| 4. | | 27. | 77. | | | | | NA | | |
| | Basements Upper floors | NA 12 a/c | | | | NA NA | | | MR | |

Do h

| | Fire Extinguishers | | | | | | | | MR | |
|-----|--|-----------|-------------------|---------|---------------------------------------|----------------|---------|----------------|------|---|
| + | Total numbers | | 2 nos. each floor | | Provided CO ₂ , ABC, Water | | | 2 | MR | _ |
| - 1 | Types | | & ABC | | CC | 2, ABC, W | ater Co | - | MR | _ |
| - 1 | IS marking | ISI | marked | | Pro | ovided | | | 1411 | |
| | Cinc Aid Hose Reels | | | | | | -14 | D 1 | | |
| - | Total numbers on each floor | No. | | | vided | MR MR | | | | |
| | Length of hose reel hose | | 30 m | | | vided | M | _ | | 7 |
| | Nozzle diameter | | 5 mm | | Pro | vided | IVI | IX. | | - |
| | Automatic fire detection and alarm | ning s | ystem | 1 | | | | N/A | | 1 |
| | Type of detectors | | N/A | N/ | | T/A | | N/A | | Ť |
| | Location of Main Panel | | N/A | 127/ | _ | N/A | | N/A | | 1 |
| | Location of Repeater Pane | 1 | N/A | N/ | | | | N/A | | 1 |
| | Alternate source of power | | N/A | N/ | A | N/A | | N/A | | + |
| | Hooters' Location | | N/A | 11.5 | | 10.275.754.05C | | | | + |
| 3. | MOEFA | | Required | 300.000 | ovid | 100 years | | MR MR | | - |
|). | Public Address System | | Required | Pr | ovid | ed | | MIN | | + |
| 0. | | NIA | | N/ | ^ | | | NA. | | + |
| | Basements | NA N/A | | | 21077 | | | N/A | | 1 |
| | Upper Floor Control of the | N/A | | | N/A N/A | | | N/A | | + |
| | Sprinkler above false ceiling | INIA | | 14 | Λ | | | | _ | 1 |
| 11. | Internal Hydrants | | | ! | | | | - | | 1 |
| - | Size of riser/down- comer | | Required | | Pr | ovided | | MI | 2 | 1 |
| | Number of hydrants per fl | | | ck | Pr | ovided | | MI | ξ. | ~ |
| | Hose Box | | 01 No. | Provi | ided | | | | M | R |
| 12. | Yard Hydrants | | | | | | | | | |
| | Total number of hydrants | · - | Required | | rovi | | | MI | | |
| | Hose Box | | Required | Pr | ovid | led | | MI | ξ. | |
| 13. | | | | | | | | | | |
| | Ground Level | | NA | | | N7.4 | - 15 | | | |
| | Discharge of main pump Head of main pump | | NA NA | | NA NA | | | NA . | | _ |
| | Head of main pumpNumber of main pumps | | NA NA | | $\overline{}$ | NA NA | | NA NA | | |
| | > Jockey pump out put | | NA | | _ | NA | | | - | |
| | > Jockey pump head | | NA | | - | NA | | ΝA | | |
| | Standby Pump out put Standby Pump Head Auto Staring/Manual stopping Pump House Access | | NA | | - | NA · | | NA NA | | - |
| | | | NA | | | NA NA | | NA NA NA | | |
| | | | | | | | | | | _ |
| | | | | | | | | | | |
| | Terrace level | | | | | | | 1/1 | | |
| | Discharge of pump | | 450 lpm | Pro | vide | d | 1 | MR | | _ |
| | Head of the pump | | 40m | Prov | _ | | | MR | | |
| | Power supply Auto starting of pump | 0 | Required | Prov | | | | MR | | - |
| 1.4 | | | Required | Prov | | 014 | | MR | | - |
| 14 | - The storage for the fig | | | | | | | .,,,,, | - | |
| | Under ground tank capacity | 2,00 | ,000 ltrs Provide | | vided | | MF | MR | | |
| | L Drow of same | Reg | equired Pr | | | Provided | | | | |
| 34 | > Draw of connection | 1700 | | P | IOVI | uea | M | R | | |
| 14 | Fire service inlet | | | | | dad | | - | | |
| 24 | | Req | uired uired | P | rovi rovi | 18252100 | M | R | | |

EXI

1m /w

| | Exit Signage | Requi | ired | Provi | ded | | MR | |
|------|--|-------|----------------------|------------|--|-------|-----|--|
| 15 | Provision of Lifts Provision of Lift Shafe | A 1 | N/A N | | N/A N/ | | 7 | |
| 16. | Provision of Litts Pressurization of Lift Shafe | | N/A | | N/A | N/A | | |
| | - igotion of fill loop | , . | Required | i | Provided | | MR | |
| | a munication in the Car | 3 | Required | d Provided | | MR | | |
| | Communication Fireman's Grounding Switch Lift Signage | | Required Required | | Provided MR DG Set MR | | | |
| | | | | | | | 2 | |
| 17. | Standby power supply | - | | | C = - | | N/A | |
| 18. | - 1 c - A =02 | | N/A | | N/A | | N/A | |
| 10. | | | N/A | | N/A | 19774 | | |
| 5562 | Fire control room | | | | NI/A | | N/A | |
| 9. | > Detector system paner > Flow Switch Panel > PA System Panel > Battery backup > Ruilding Floor Plans Re | | | | N/A | | N/A | |
| | | | N/A N/A N/A Required | | N/A | N/A | | |
| - | | | | | Provided | N/A | | |
| | | | | | Provided | MR | | |
| | | | | | Provided | MR | | |
| 20. | Special Fire Protection Systems for Protection of special Risks, if any; | Requ | | | 2 fire extinguishe vided near electri | | | |

The fire protection systems provided in the building were test checked and found

functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter No. F6/DFS/MS/CGHS/2018/SZ/163, dated as required under the rules the FSC issued vide letter No. F6/DFS/MS/CGHS/2018 recommended. If 24/01/2018 renewal under Rule 37 of the Delhi Fire Service Rules 2010 is recommended. If approved FSC may be issued.

Note: Photographs are placed c/ to c/

Signature of the Inspecting Office

Name: Udai Vir Singh Designation: ADO/DWK

19/11/11

20 11 20m

Julax anym