0/27

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/School/WZ/2024/ 1138

Dated: 26 / 11 /2024

Director

FIRE SAFETY CERTIFICATE

Certified that the Govt. Girls Sr. Sec. School No-1, (School ID-1514012) Located at Khyala, New Delhi-110018, Two blocks are comprised of ground +01 Upper Floor & Two blocks are comprised of ground floor only, owned/occupied by Govt. Girls Sr. Sec. School vide No-1, issued FSC by this department was already F6/DFS/MS/School/MN/2021/664 dated 27/08/2021. The premises was re - inspected by the officer concerned by this department on 13/11/2024 in the presence of Smt. Rasmeet Kaur (Principal) and found that the fire safety arrangements/ equipments provided in the building found in good working condition. That the building/premises have deemed complied with fire prevention and fire safety requirements in accordance with the circular No. F-16/Estate/CC/Fire safety/2011/3298-3398 dated 01/03/2011 and the building/ premises is fit for occupancy class "Educational" (Group -B) with effect from 26.111 12021 for a period of three years subject to the conditions mentioned below.

Issued on ... 26 11 2024 at New Delhi.

Copy to:

 The Principal, Govt. Girls Sr. Sec. School No-1, Khyala (School ID-1514012) Located at Khyala, New Delhi-110018, Email Id-ggssskhyala1514012@gmail.com

2. Director of Education, GNCT of NCT of Delhi, Old Secretariat.

Following fire safety directives must be adhered to:-

 All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

 Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any

 The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1/m

| | INSPECTION REPORT | | | | | | |
|-------------------------|---|--|---------------|-----------------------|-------------------|--|--|
| 1. | Name & address of the building | Govt. Girls Sr. Se | | | a, New Dell | | |
| | | 110018, (School ID- | 1514012) |) | | | |
| 2. | Type of Occupancy | Educational Four blocks (Two Blocks Ground floor only Two block are ground + One Upper Floor) Renewal | | | | | |
| 3. | Type of Case | | | | | | |
| 4. | Details of previous NOC | F6/DFS/MS/School/ | MN/2021/ | 664 dated 27/08 | 3/2021 | | |
| | Fire Safety directives letter No | DOE circular No 3298-3398 dated 01/03/2011 | | | | | |
| | Date of inspection | 13/11/2024 Sarabjeet Singh ADO (MN) | | | | | |
| | Name of the Inspecting Officers | | | | | | |
| | Name and designation of | Smt. Rashmeet Kaur | (Principal |) | | | |
| (37.37.) | officers from the building side | | | | (00/2021) | | |
| 9. Year of Construction | | 1976 (As per Previous Inspection report dtd 18/08/2021) | | | | | |
| 10. | Applicant's letter No. | Email dated 04/11/2 | | | 2024 | | |
| S. No. | Minimum Standards on fire prevention and fire safety U/R 33 | Required as per Rule of DFS Rule 201 | e 35(6) 10 | Provided at site | Remarks MR/NMR | | |
| 1 | Access to building | | | | | | |
| • | Road width | Accessible | | Provided | MR | | |
| | Gate width | Accessible | F | Provided | MR | | |
| | Width of internal road | NA | | NA | NA | | |
| 2 | Number, Width, Type & Arrang | ement of Exits | | | | | |
| | a. Number of staircases | | | | | | |
| | Upper Floors | 02 | P | Provided | MR | | |
| | Basements | NA | | NA | NA | | |
| | Width of staircases Upper Floors | 1.5 mts each | | 2X150cms, Block | | | |
| | Basements | NA | | NA | NA | | |
| | c. Protection of exits | | | | | | |
| | Fire check door | NA | In a li | NA | NA | | |
| | Pressurization | NA | | NA | NA | | |
| | e. No. of continuous staircases to ter | | - | NA | NA MB | | |
| | f. Width of Corridor | 1.5 Mtr. | 4 | rovided m Provided | MR MR | | |
| | g. Door Size | 1m | 2X1 | m Provided | MIK | | |
| 3 | Compartmentation. | NA | | NA | NA | | |
| | • Fire check door | NA NA | | NA | NA | | |
| | Sealing of electrical shafts Fig. Paties of shaft door. | NA | | NA | NA | | |
| | Fire Rating of shaft door Water Curtain | NA NA | | NA | NA | | |
| | Water Curtain Fire Dampers | NA | | NA | NA | | |
| 4 | Smoke Management System. | | | | | | |
| | Basements | NA | | NA | NA | | |
| 22 | Upper floors | NA | | NA | NA | | |
| 5 | Fire Extinguishers | | | | | | |
| | Total numbers | 07 nos. | F | Provided | MR | | |
| | Types | CO ₂ , ABC type | 5 A | BC, 2 CO ₂ | MR | | |
| | IS marking | ISI marked | g <u>_</u> I | Provided | MR | | |
| | | | | | . diam | | |
| | | | 200 | | | | |

| 6 | First Aid User De L | | | V. | | | |
|-----|--|---------------------|----------|----------|--|--|--|
| 0 | First-Aid Hose Reels. • Total numbers on each floor | NA T | NA | NA 1 | | | |
| | Length of hose reel hose | NA NA | NA | NA | | | |
| | Nozzle diameter | NA | NA | NA | | | |
| 7 | Automatic fire detection and alarming system. | | | | | | |
| | Type of detectors | NA | NA | NA | | | |
| | Location of Main Panel | NA | NA | NA | | | |
| | Location of Repeater Panel | NA | NA | NA | | | |
| | Alternate source of power | NA | NA | NA | | | |
| | Hooters' Location | NA | NA | NA | | | |
| 8 | MOEFA | NA | NA | NA | | | |
| 9 | Public Address System. | NA | NA | NA | | | |
| 10 | Automatic Sprinkler System. | | | | | | |
| | Basement | NA | NA | NA. | | | |
| | Upper Floor | NA | ÑĀ | NA | | | |
| | Sprinkler above false ceiling | NA | NA | NA | | | |
| 11 | Internal Hydrants | | | 1 | | | |
| | Size of riser/down-comer | NA | NA | NA | | | |
| | Number of hydrants per floor | NA NA | NA | ÑA | | | |
| | Hose Box | NA NA | NA | NA | | | |
| 12 | Yard Hydrants. | INA | | - | | | |
| | Total number of hydrants | NA | NA NA | NA | | | |
| | Hose Box | NA | NA NA | NA | | | |
| 3 | | | | 110 | | | |
| 3 | Pumping Arrangements. Ground Level | | | | | | |
| | ➤ Discharge of main Pump | | | - | | | |
| | Head of Main pump | NA | NA NA | NA | | | |
| | > Number of main pumps | NA NA | NA | - NA | | | |
| - 1 | > Jockey Pump out put | NA NA | NA | NA | | | |
| | > Jockey pump head | NA NA | NA NA | NA | | | |
| | Standby Pump out put | NA NA | NA NA | NA | | | |
| | Standby Pump Head | NA | NA NA | NA NA | | | |
| - 1 | > Auto Starting/ Manual stopping | NA NA | NA NA | NA NA | | | |
| - 1 | > Pump House Access | NA NA | | NA | | | |
| | Terrace level | NA . | NA | NA NA | | | |
| | 1925 SERVING SERVING | NA | T NA | 1 374 | | | |
| | | NA NA | NA NA | NA. | | | |
| | | NA NA | NA NA | NA NA | | | |
| | | Section and Control | NA NA | NA NA | | | |
| + | Tanto State ting of painty | NA | NA | NA | | | |
| 10 | Captive Water Storage for fire fighting. | Total at a | 9 | | | | |
| | Underground tank capacity | NA | NA | NA | | | |
| | ▶ Draw-off connection | NA | NA | NA | | | |
| | ➤ Fire service inlet | NA | NA | NA | | | |
| | > Access to tank | NA | NA NA | NA NA | | | |
| | Overhead Tank capacity | NA | NA NA | NA NA | | | |
| E | xit Signage. | NA | NA | | | | |
| - | | *163 | INA , | NA | | | |

000

| _ | | 4114 | 100 | | | | |
|-----|---|------|-----|----|--|--|--|
| P | rovision of Lifts. | | | | | | |
| | Pressurization of Lift Shaft | NA | NA | NA | | | |
| ¥ | Pressurization of Lift lobby | NA | NA | NA | | | |
| | Communication In lift Car Fireman's Grounding Switch Lift Signage | NA | NA | NA | | | |
| | | NA | NA | NA | | | |
| _ \ | | NA | ŇA | NA | | | |
| 7 | Standby power supply | NA | NA | NA | | | |
| 8 | Refuge Area. | | | | | | |
| | > Total Area | NA | NA | NA | | | |
| | > Location | NA | NA | NA | | | |
| 19 | Fire Control Room | | | | | | |
| | Detector System Panel | NA | NA | NA | | | |
| | Flow Switch Panel | NA | NA | NA | | | |
| | PA System Panel | NA | NA | NA | | | |
| | Batter backup | NA | NA | NA | | | |
| | Building Floor Plans | NA | NA | NA | | | |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any: | NA | NA | NA | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/School/MN/2021/664 dated 27/08/2021, renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer Sarabjeet Singh ADO (MN)

Joyann Sir, F. T is put upper oual & Synahu please. 1