GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2024/ 697

Dated: 27 /11 /2024

FIRE SAFETY CERTIFICATE

Certified that the Lok Kalyan Samiti, at Sucheta Bhawan, 11-A Vishnu Digamber Marg , New Delhi, comprises of front side block Ground and three upper floor and rear side block basement, ground, mezzanine and four upper floor was earlier granted FSC vide letter no. F6/DFS/ MS/NDZ/2022/130 dated 25.03.2022. Now, the premises was re-inspected by officers concerned of this department on 14.11.2024 in the presence of Sh. Bharat Bhushan and found that the said premises has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Business Building (Day care eye center & Office), Group- E with effect from Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule

Delhi Fire Service

Copy to:-

1. The Commissioner, MCD, Civic Centre, New Delhi.

2. Authorised Signatory, LKS, Sucheta Bhawan, 11-A Vishnu Digember Marg, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 9. Any flammable material for interior decoration is strictly prohibited.

INSPECTION REPORT

1. Name & address of the building : Lok Kalyan Samiti, Sucheta Bhawan,

11-A, Vishnu Digamber Marg,

New Delhi-110002.

: Business Building Day care eye center & 2. Type of occupancy

Office Front side - Ground + 03 Upper

floors Rear Side - B+ Gr. + Mezzanine floor + 04

Upper floors

: renewal 3. Type of case:-

Details of previous NOC /clearance : F6/DFS/ MS/NDZ/2022/130 dated

25.03.2022

5. Fire safety directives No.

: N/A

6. Date of inspection:-

: 14/11/24

7. Name of the inspecting officer

Sh. Rajinder Atwal(DO/CD) & Sh. Ravinder Singh ADO/CC

8. Name & designation of officer From the building side

: Sh. Bharat Bhushan (Asstt. Manager)

9. Year of construction

: old : letter no. LKS/GEN/2024/Renewal FSC/41

| 10. | Applicant's letter No | : letter no. dated 11. | LKS/GEN/2024/Re 10.2024. | |
|----------|---|---|-----------------------------|-------------------|
| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement/ Existing fire safety arrangements | Provided at site | Remarks MR/NMR |
| 1. | Approach to Building | | | MR |
| | 1) Road width | 09 mtr. | 12 Mtr. | NA |
| | 2) Gate width | NA | 4.5 mtr. | |
| | 2)Width of internal road | NA | NA | NA |
| 2. | Number, Width Type & Arra | ngement of Exit | S | |
| ۷. | A. Number of staircases | | | I v m |
| | 1. Upper floors | 02 Nos. | 03 Nos. | MR |
| | 2. Basements | 01 Nos. | 02 Nos. | MR |
| | B. Width of staircase | | |) (D |
| | 1. Upper floors | 1. mtr.&1.20 mtr. | 1.50 mtr. & 1.20 mtr. | MR |
| | 2. Basements | 1.20 mtr. | 1.20 mtr. | MR |
| | C. Protection of exits | | | 274 |
| | 1. Fire check door | NA | NA | NA |
| | 2. Pressurization | NA | NA | NA |
| | D. No. of continuous staircase to terrace | NA | NA | NA |
| | E. Width of corridor | NA . | NA | NA |
| | F. Door size | 01 mtr. | 01mtr. | MR |
| | Compartmentation | | | |
| <i>,</i> | 1) Fire check door | NA | NA | NA |
| | 2) Sealing of electrical shafts | Required | Provided | MR |
| | 3) Fire rating of shaft door | NA | NA | NA |
| | 4) Water curtain | NA | NA | NA |
| | 5) Fire Dampers | NA | NA | NA |
| . 1 | Smoke Management System | | | |
| | 1) Basements | 12 ACPH | Exhaust fan | MR |
| Ì | 2) Upper floors | 12 ACPH | Natural | MR |
| 27 | Fire Extinguishers | | | 1 |
| | 1) Total numbers | 20 Nos. | 25 Nos. | MR |

| | | 1400 000 | ABC, CO2 | MR | |
|----|--|----------|--|---------|--|
| | 2) Types | ABC, CO2 | Provided | MR | |
| | 3) ISI marking | Required | Flovided | | |
| | First-Aid Hose Reel | | Drawidad | MR | |
| | 1)Total number at each floo | | Provided | MR | |
| | 2) Length of hose reel hose | 30 m | 30 m | MR | |
| | 3) Nozzle diameter | 5 mm | 5 mm | IMIK | |
| 7. | Automatic Fire Detection & Alarming System | | | | |
| | 1) Type of detectors | NA | NA | NA | |
| | 2) Location of main panel | NA | NA | NA | |
| | 3) Location of repeater pane | | NA | NA | |
| | 4) Alternate source of power | NA | NA | NA | |
| | 5) Hooter's Location | NA | NA | NA | |
| | MOEFA | Required | Provided | MR | |
| | Public Address System | Required | Provided | MR | |
| 0. | Automatic Sprinkler System | | | 100 | |
| | 1) Basement | Required | Provided | MR | |
| | | NA | NA | NA | |
| | 2) Upper floors | NA NA | NA NA | NA | |
| | Sprinkler above false ceiling | NA . | TAA . | 255 | |
| 1. | Internal Hydrants | | 1 | MR | |
| | 1) Size of riser/down-comer | 100 MM | Provided | IVIIX | |
| | 2) Number of hydrants per | 02 | 02 | MR | |
| | Basement | | | MR | |
| | 3) Hose box each floor | 02 | 02 | MK | |
| 2. | Yard Hydrants | | Too | N/A | |
| | 1) Total number of hydrants | N/A | V- | N/A | |
| | 2) Hose box | N/A | 02 | IVA | |
| 3. | Pumping Arrangement | | | | |
| | Ground level | | D | N/A | |
| | a) Discharge of main pump | N/A | Boosting pup to replenish to OHT | N/A | |
| | b) Head of main pump | N/A | N/A | N/A | |
| | c) Number of main | N/A | N/A | N/A | |
| | pump | N/A | N/A | N/A | |
| | d) Jockey pump out put | N/A | N/A | N/A | |
| | e) Jockey pump head f) Stand by pump | N/A | N/A | N/A | |
| | output g) Stand by pump head | N/A | N/A | N/A | |
| | h) Auto | N/A | N/A | N/A | |
| | starting/Manual stopping | | | | |
| | 2) Terrace level | | | | |
| | a) Discharge of pump | 900 lpm | Provided | MR | |
| | b) Head of pump | 35M | Provided | MR | |
| | c) Power supply | Required | Provided / | MR | |
| | d) Auto starting of | Required | Provided | MR | |
| | Captive Water Storage for Fire | | | | |
| | Under ground tank | 30,000 | 30,000 ltr. | MR | |

| | a) Draw-off connection | Required | Provided | MR |
|-----|-------------------------------------|-------------------|---------------------|----------|
| | b) Fire service inlet | Required | Provided | MR |
| | professional and special beautiful | Required | Provided | MR |
| | d) Over head tank | 20,000 litr. | 20,000 litr. / | MR |
| | capacity | Required | Provided | MR |
| 15. | Exit Signage. | Required | | |
| 16. | Provision of Lifts. | | DI/A | N/A |
| | a) Pressurization of lift shaft | N/A | N/A | ANTWE SE |
| | b) Pressurization of lift | N/A | N/A | N/A |
| | lobby | Required | Provided | MR |
| | c) Communication in | Required | I The second second | |
| | lift car | Required | Provided | MR |
| | d) Fireman's switch | Required | Provided | MR |
| | e) Lift signage | | Provided | MR |
| 17. | Stand by Power Supply | Required | NA | NA |
| 18. | Refuge Area | NA | 1 | NA |
| 10. | Total area location | NA | NA | INA |
| | | NA | NA | NA |
| 19. | Fire Control Room | | NA | NA |
| | a) Detector system panel | NA | NA. | |
| | | 314 | NA | NA |
| | b) Flow switch panel | NA | NA NA | NA |
| | c) PA system panel | NA | NA NA | NA |
| | d) Battery backup | NA | M | |
| | e) Building floor plan | NA- | NA | NA |
| | Special Fire Protection System | | special Risk, if | N/A |
| 20. | Special Fire Protection System any: | IOI FIOLECTION OF | AL STANDED HOUSE | |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules the FSC issued vide letter no. F6/DFS/MS/NDZ/2022/130 dated 25.03.2022, renewal under rule 35(6) of the Delhi Fire Service rules 2010, Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name :- Rajinder Atwal

Designation :- DO (CD)

Signature of the Inspecting Officer

Name :- Ravinder Singh Designation :- ADO (CC)

75.01

Director My

Aory