

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2024/476

Dated: 43/12/2024

FIRE SAFETY CERTIFICATE

Certified that the M/s Gush International located at 626, 627,631 (Part) Bawli Chowk, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (Reception + 02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor), total 14 guest rooms up to third floor owned/occupied by M/S Gush International was granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2021/397 dated 16/09/2021. Now, the premises was re-inspected by the officer concerned of this department on 20/11/24 in the presence of Mr. Kisan and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (Reception + 02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor), Total -14 guest rooms up to third floor only, and valid up to the period of three year from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued .. 0.3 112 202 at New Delhi by.

OIRECTOR Demi Fire Service

Copy to:-

- 1. The Commissioner, North DMC, Civic Centre, New Delhi: ensure the occupancy in the building.
- The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID NO. 2024110916626 dated 09.11.2024.
- The Manager, M/S Gush International 626, 627,631 (Part) Bawli Chowk, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house up to third floor only.
- Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- The compliance with regards to electrical installation, structural stability, set back area, occupancy
 and any deviation in construction etc. shall be verified from authority concerned.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape such as staircase, exits, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT 30

1. Name & address of the building M/s Gush International at 626, 627 631 (Part)

2. Type of occupancy:
Bawli Chowk, Pahar Ganj, New Delhi
Residential, Sub Division-A-1

Ground + 03 Upper floors (total 14 guest rooms)
Ground floor (Reception + 02 guest rooms),

1st floor to 3rd floor (04 guest rooms at each floor)

3. Type of case:- Renewal

4. Details of previous FSC:- No. F6/DFS/MS/GH/NDZ/2021/397 dated

16/09/2021.

5. Fire safety directives No.-6. Date of inspection:-20/11/24

7. Name of the inspecting officer:- Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer

From the building side:- Mr. Kishan
9. Year of construction:- 2009

10. Applicant's letter No:- ID NO. 2024110916626 dated 09.11.2024.

| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement/ Existing fire safety arrangements | Provided at site | Remarks MR/NMR PSP area |
|-------|--|--|------------------|-------------------------------|
| 1. | Access to Building | | | 3771 |
| | 1) Road width | N/A | N/A | N/A |
| | 2) Gate width | N/A | N/A | N/A |
| | 3) Width of internal road | N/A. | N/A | N/A |
| 2. | Number, Width Type & Ar | rangement of Ex | its | |
| 4. | A. Number of staircases | | | 1.00 |
| | 1. Upper floors | 01 No. | 01 No. | MR |
| | 2. Basements | N/A | N/A | N/A |
| | B. Width of staircase | | / | MR |
| | 1. Upper floors | 0.80 mtr. | 1.25 mtr. | N/A |
| | 2. Basements | N/A | N/A | IVA |
| | C. Protection of exits | | 27/4 | N/A |
| | 1. Fire check door | N/A | N/A | N/A |
| | 2. Pressurization | N/A | N/A | MR |
| | D. No. of continuous | 01 | 01 | IVIK |
| | staircase to terrace | 27/1 | N/A | N/A |
| | E. Width of corridor | N/A | 01 mtr. | MR |
| | F. Door size | 01 mtr. | or mu. | IVIIC |
| 3. | Compartmentation | | NIA | N/A |
| | 1) Fire check door | N/A | N/A | N/A |
| - 7 | 2) Sealing of electrical shafts | N/A | N/A | N/A |
| | 3) Fire rating of shaft door | N/A | N/A | N/A |
| | 4) Water curtain | N/A | N/A | N/A |
| | 5) Fire Dampers | N/A | N/A | IMPL |
| 1. | Smoke Management System | F | INI/A | N/A |
| | 1) Basements | N/A | N/A Drawided | MR |
| | 2) Upper floors | Required | Provided | IVAIN |
| 5. | Fire Extinguishers | | | 10 |
| | 1) Total numbers | 08 Nos. | 08 Nos. | MR |
| - | 2) Types | ABC & CO2 | ABC & CO2 | MR |

| | 3) ISI marking | Required | Provided | MR |
|-----|---|--------------|-----------------------|-------|
| 6. | First-Aid Hose Reel | | | |
| | 1) Total number of eachfloo | r 01 | 01 | MR |
| | 2) Length of hose reel hose | 30 mtr. | 30 mtr. | MR |
| | 3) Nozzle diameter | 05 mm | 05 mm | MR |
| 7. | Automatic Fire Detection | / 100 | | |
| | 1) Type of detectors CO typ | | Provided / | MR |
| | 2) Location of main panel | Ground | Provided | MR |
| | 3) Location of repeater pane | | N/A | N/A |
| | 4) Alternate source of power | | Provided | MR |
| | 5) Hooter's Location | Ground | Provided | MR |
| 8. | MOEFA | Required | Provided | MR |
| 9. | Public Address System | Required | Provided | MR |
| 10. | Automatic Sprinkler System | | Flovided | IVIIX |
| 10. | 1) Basement | N/A | N/A | N/A |
| | 2) Upper floors | N/A N/A | N/A N/A | N/A |
| | 3) Sprinkler above false ceili | | | N/A |
| 11. | Internal Hydrants | ng N/A | N/A | IN/A |
| 11. | 1) Size of riser/down-comer | I NI/A | NI/A | N/A |
| | | N/A | N/A | N/A |
| | Number of hydrants per floor | N/A | N/A | N/A |
| | 3) Hose box | N/A | N/A | N/A |
| 12. | | I N/A | N/A | I N/A |
| 12. | Yard Hydrants | I NI/A | I NI/A | LNIA |
| | Total number of hydrants Hose box | N/A | N/A | N/A |
| 12 | | N/A | N/A | N/A |
| 13. | Pumping Arrangement | NIA | N/4 | 27/4 |
| | 1) Ground level | N/A | N/A | N/A |
| | a) Discharge of main | N/A | N/A | N/A |
| | b) Head of main pump | 37/4 | 13774 | 1 |
| | b) Head of main pump | N/A | N/A | N/A |
| | c) Number of main pum | | N/A | N/A |
| | d) Jockey pump out put | | N/A | N/A |
| | e) Jockey pump head f) Stand by pump output | N/A t N/A | N/A | N/A |
| | | N/A | N/A N/A | N/A |
| | g) Stand by pump head | | | N/A |
| | h) Auto starting/Manual | IN/A | N/A | N/A |
| | stopping 2) Terrace level | | + | |
| | | 225 LPM | 225 LPM | MD |
| | a) Discharge of pump b) Head of pump | 30 mtr. | 30 mtr. | MR |
| | | Required | Provided | MR |
| | c) Power supply | | Provided | MR |
| 4. | d) Auto starting of pump | | Flovided | MR |
| 4. | Captive Water Storage for 1 | 1 | | |
| | Under ground tank capacity | N/A | N/A | N/A |
| | a) Draw-off connection | N/A | N/A | N/A |
| | b) Fire service inlet | Required | Provided | MR |
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank capacity | 2500 ltr. | 2500 ltr. Old case | MR |
| 5. | Exit Signage. | Required | Provided | MD |
| J. | DAN OIGHAGE. | Required | Flovided | MR |

| 16. | Provision of Lifts. | | | |
|-----|--|----------|----------|------|
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided | / MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System for Protection of special Risk, if any: | | | N/A |

The above fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter No. F6/DFS/MS/GH/NDZ/2021/397 dated 16/09/2021, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, DFA is prepared and put up for kind perusal/approval please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)