

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/EH/2024/SZ/389

Dated: 03/12/2024

FIRE SAFETY CERTIFICATE

Certified that the Eating House in the name & style of M/s OLIVE BAR & KITCHEN PVT LTD located at Haveli No 6 & 8, One Style Mile, Kalka Das Marg, Mehrauli, New Delhi- 110030 comprised of ground and half floor of the building and the restaurant is running at ground floor only owned/occupied by (A Unit of Olive Bar & Kitchen Pvt Ltd) was issued FSC by this department vide letter no F6/DFS/MS/EH/2021/SZ/352 dated 02/12/2021. The restaurant premise was reinspected by the officer concerned of this department on 27/11/2024 in the presence of Mr. P. J Thareja (owner) and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class D "Assembly Building" (Restaurant at ground floor only) and validity upto 31/03/2027 in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 03/12/2024 at New Delhi by

(ATUL GARG) DIRECTOR

DELHI FIRE SERVICE

Copy to: -

 The Joint Commissioner of Police (Lic.), 1st Floor, P.S. Defence Colony, New Delhi-49. (Ref. MCD Portal ID 2024112017048 dated 20/11/2024)

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- All the staff members must know the correct method of operation of fire-fighting system.
- The owner/occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

	INSPECTION	DEDODE				
1	Name & Address of the Building M/s OLDER (1.11) To a Vitable Pvt					
	M/s OLIVE (A Unit of Olive Bar & Kitchen Ltd) Plot No 6 & 8, One Style Mile, Kalka I					
2	Type of Occupancy	Marg. Mehrauli No	Kains -			
3		Marg, Mehrauli, New Delhi- 110030 Group-D Assembly Building.				
4	Building Comprised of	Ground and Half upper floor				
ě .	Type of Case	Renewal	774	-1.1		
5	Details of Previous NOC	F6/DFS/MS/EH/20	021/SZ/352 dated 02/	12/2021		
6	Fire Safety Directives Letter No	Nil				
7	Date of Inspection	27/11/2024	Tright of the Co			
8	Name of the Inspecting Officers		Sh. Rajesh Kumar, ADO (BCP)			
9	Name & Designation of Officers	Mr. P. J Thareja (owner)				
	from the building side	M. 1.3 Hadya (Wild)				
10	Year of construction	1960				
11	Applicant letter No.	Mcd Portal ID 202	4112017048 dated 20	0/11/2024		
. No.	Minimum standards on Fire Prevention					
ie in deser	and Fire Safety U/R 33	Old NOC	Provided at Site	MR/NMR		
1	Access to Building.	Requirement		WHOTHER		
	Road width	Domin 4	9m	MR		
	Gate width	Required 02 Exit	Provided	MR		
	The state of the s		N/A	N/A		
2	Width of internal road	N/A	N/A	IVA		
2	Number, width, type & arrangement of ex	cits.	man i manay e	1		
	a) Number of Staircase	and the				
	➤ Upper floors.	N/A	02 Nos Provided	N/A		
	➤ Basement floor.	N/A	N/A	N/A		
	b) Width of Staircase					
	> Upper floors	N/A	N/A	N/A		
	> Basement floor	N/A	N/A	N/A		
	c) Protection of exits		Total Parketing			
	Fire check door	N/A	N/A	N/A		
	> Pressurization	N/A	N/A	N/A		
	d) No. of continuous staircase to terrace		N/A	N/A		
	e) Width of corridor	N/A	N/A	N/A		
	1 Door size	1.50 m (old case)	02 Nos Provided	MR		
3	Compartmentation.					
	Fire check door.	N/A	N/A	N/A		
-	Sealing of electrical shafts.	N/A	N/A	N/A		
	Fire rating of shaft door.	N/A	N/A	N/A		
- 1	Water curtain	N/A	N/A	N/A		
1	Fire dampers.	N/A	N/A	N/A		
4	Smoke Management system.		61 134 and	ANT I		
	Basement	30 ACPH	N/A	N/A		
	Upper floors	12 ACPH	Exhaust Fan Provide	=200000		
5						
-		12 Nos	Provided	MR		
1	Total numbers	ABC/CO ₂	ABC, Foam & CO ₂	MR		
	• Types	ISI marked	Provided	MR		
_	ISI Marking	151 marked	Flovided	MK		
-	First Aid Hose Reels. Total numbers on each floor.	One	03 Nos	MR		
	Length of hose-reel hose.	30m	Provided	MR		
	 Length of nose-reel nose. 	2011				
	1/5/	Smm	Provided			
	Nozzle Diameter	5mm	Provided	MR		
	1/5/	M-GSC-W	Provided N/A	MR N/A		

	-bloom				_	
	Location of Repeater Panel	N/	A	I/A		
	Alternate source of power	N/A	A N	I/A		
	Hooter's location	N/A	1	N/A Provided NA		
		Requi	D. au			
8		N/A	3.1			
9		IN/A				
10	Automatic Sprinkler System	N/A	N/.	A	N.	
	Basement	N/A		Provided		
	Ground floor.	N/A	N/A	/=/	N/	
	 Sprinkler above false ceiling 	N/A				
11	Internal Hydrants.	100	n Provid	led	MI	
	Size of Riser/Down-comer	100 mm		Provided		
	 Number of Hydrant per floor 	One	Provid		MR	
	Hose box.	One	110			
12	Yard Hydrants.		N/A		N/A	
	Total number of hydrants.	N/A	N/A		N/A	
	Hose box.	N/A	IVA			
13	Pumping arrangements.					
	Ground Level	(-A - D) (Provided	i	MR	
	Discharge of main pump.	450 LPM	Provided		MR	
	Head of main pump.	35 m	Provided		MR	
	Number of main pumps.	01	N/A		N/A	
	> Jockey Pump output.	180 LPM	N/A		N/A	
	> Jockey Pump head.	35 m	N/A	- 1	N/A	
	Standby Pump output.Standby Pump head.	N/A	Provided	-H	MR	
	a A famual Stanning	Required			MR	
	 Auto Starting/Manual Stopping. Pump house access. 	Required	Provided		MIK	
					27/4	
	Terrace Level Discharge of pump.	N/A	N/A		N/A	
	Head of pump.	N/A	N/A		N/A	
	> Power supply.	N/A	N/A		N/A	
	Auto starting of pump.	N/A	N/A		N/A	
14	Captive water storage for fire fighting.					
14	Underground tank capacity.	5,000 ltrs	25,000 ltrs		MR	
	> Draw-off connection.	N/A	N/A		N/A	
	> Fire Service Inlet.	Required	Provided		MR .	
	> Access to tank.	N/A	N/A		I/A	
	Overhead tank capacity.	N/A	N/A		I/A	
15	Exit Signage.	Required	Provided	I N	IR .	
16	Provision of Lifts.	5-71	N//A	NT.	/A	
	Pressurization of lift shaft.	N/A	N/A N/A	N/	ARTON	
	Pressurization of lift lobby.	N/A	N/A N/A	N/		
	Communication in lift car.	N/A N/A	N/A N/A	N/		
	• Fireman's switch.	N/A	N/A	N/A		
7	Lift signage. Standby Power Supply	Required	Provided	MF		
7 8	Refuge Area	1	1000 A			
ď		N/A	N/A	N/A		
	Total area Location	N/A N/A	N/A N/A	N/A		
\exists	Location Fire Control Room.	IVA	IVA	IV/A		
)	Detector system panel.	N/A	N/A	N/A		
	Flow switch panel.	N/A	N/A	N/A		
	PA system panel.	N/A	2/40/202	1		
		7.1	N/A	N/A		

W 22

	Battery backup.	N/A	N/A	N/A
	 Building floor plan. 	N/A	N/A	N/A
20	Special Fire Protection System for the Protection of special Risk, if any.	N/A	N/A	N/A

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/EH/2021/SZ/352 dated 02/12/2021, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar Designation: ADO (BCP)

DO (SD)

Mulerming

c60 (HB)

Dinester his

The poly

03/12/14

Ms cell

05/12/24 05/12/24