GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001**

No.F6/DFS/MS/GH/NDZ/2024/ 484

Dated: 05.1.12.12024

FIRE SAFETY CERTIFICATE

Certified that the Shree Sai Dham Dx. Guest House located at 3228, School Lane, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (reception), 1st floor to 3rd floor (05 guest rooms at each floor), total 15 guest rooms up to third floor owned/occupied by Shree Sai Dham Dx. Guest House was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2021/533 dated 17/12/2021. Now, the premises was re-inspected by the officer concerned of this department on 28/11/24 in the presence of Sh. Saddam and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (reception), 1st floor to 3rd floor (05 guest rooms at each floor) total 15 guest rooms up to third floor only, and valid up to three year from the date of in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 05/12/2024 at New Delhi by.

DIRECTOR Fire Officer

Copy to:-

- 1. The Commissioner MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed.
- 2. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Ref. No. 2024111516829 dated 15.11.2024.
- 3. The Manager, Shree Sai Dham Dx. Guest House at 3228, School Lane, Pahar Ganj, New Delhi

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house up to third floor only.
- 2. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape such as staircase, exits, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry". 9. Any flammable material for interior decoration is prohibited

INSPECTION REPORT

1 Name & address of the building:-Shree Sai Dham Dx. Guest House at

3228, School Lane, Pahar Ganj, New Delhi.

2. Type of occupancy:-Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 15 Guest rooms) Ground floor (reception), 1st floor to 3rd floor

(05 guest rooms at each floor)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/NDZ/2021/533 dated

17/12/2021.

5. Fire safety directives No.-N/A

6. Date of inspection:-28/11/24

7. Name of the inspecting officer:-Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer

From the building side:-Mr. Saddam

	Year of construction:-	2001		- 44 2024		
10	. Applicant's letter No:-	ID No. 2024	111516829 dated 1	15.11.2024. ase (renewal		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site			
1.	Access to Building					
	1) Road width	N/A	N/A	N/A		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arr	155/330,05000	rits			
4.	A. Number of staircases		4:			
	1. Upper floors	01 No.	01 No.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	0.80 mtr.	1.13 to 1.24 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase to terrace	01	01	MR		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
3.	Compartmentation	2				
J.	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	N/A	N/A	N/A		
	2) Upper floors	12 a/c per hour	Natural Ventilation/exhaust fan	MR		
5.	Fire Extinguishers			1 m		
	1) Total numbers	08 Nos.	08 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		

Hlus

				100
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel			I.m.
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 m	30 m	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	Alarming Sys	tem	
	1) Type of detectors CO	Required	Provided	MR
	2) Location of main panel	Gr. floor	Provided	MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Each floor	Provided	MR
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
		23422		V v
	Internal Hydrants			
11.	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	Control of the contro	1 N 1 2		
	floor	N/A	N/A	N/A
	3) Hose box	1,172		
12.	1) Total number of hydrants	N/A	N/A	N/A
		N/A	N/A	N/A
	2) Hose box	1,772		
13.	Pumping Arrangement	N/A	N/A	N/A
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	IVA		
	pump	N/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	IV/A	1971	
	stopping			
	2) Terrace level	225 LPM	225 LPM /	MR
	a) Discharge of pump		30 mtr	MR
	b) Head of pump	30 mtr	Provided	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	IVIK
4.	Captive Water Storage for Fir	e Fighting		
	Under ground tank	N/A	N/A	N/A
	capacity			27/4
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacit	2500 ltr.	2500 ltr.	MR

olis

15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	required	Tiovided	IVIK
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System if any:	NA		

The above fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter No. F6/DFS/MS/GH/NDZ/2021/533 dated 17/12/2021, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, DFA is prepared and put up for kind perusal/approval please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

23/11/24

Mes pros

29/11/20

Director M

Hey C