

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2024/50

Dated: 16/12/2024

FIRE SAFETY CERTIFICATE

Certified that the Down Town Guest House located at 4583, Main Bazar, Pahar Ganj, New Delhi in a building comprised of B+ Gr. + 4 Upper floors, Ground floor (reception), 1st floor to 3rd floor (08 guest room at each floor) as above 24 guest rooms only and 4th floor not in use as per affidavit dated 15.11.2019 owned/occupied by Down Town Guest House. The FSC was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2021/521 dated 10/12/21 for ground to third floor for 24 guest room only. Now, the premises was re-inspected by the officer concerned of this department on 09/12/24 in the presence of Manager and found that the said guest house building, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (reception), 1st floor to 3rd floor (08 guest room at each floor) as above 24 guest rooms only and valid up to three year from the date of in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 16 12 2024 at New Delhi by.

Copy to:-

1. The Commissioner, MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed above and deviation if any.

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID No. 2024112217122 dated 26.11.24.

3. The Manager, Down Town Guest House, 4583, Main Bazar, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house ground to third floor only.

2. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the

3. The trained fire fighting staff should be available round the clock.

4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned. Further, basement is not a part of guest house and same shall strictly be used as stipulated in BBL concerned.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any. 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

- 7. The means of escape such as staircase, exits, corridor, etc shall be kept unobstructed / unlocked for unhindered
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. Any flammable material for interior decoration is prohibited.

N/29

INSPECTION REPORT

1. Name & address of the building:-Down Town Guest House at 4583, Main

Bazar, Pahar Ganj, New Delhi

2. Type of occupancy:-Residential (guest house)-Sub Division-A-1

B+ Gr. + 04 Upper floors (total 24 Guest rooms) Ground floor (reception), 1st floor to 3rd floor (08 guest room at each floor) 4th floor not in use

as per affidavit dated 15.11.19

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/NDZ/2021/521 dated

10/12/21.

5. Fire safety directives No.-N/A

6. Date of inspection:-09/12/24

7. Name of the inspecting officer:-Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer

From the building side:-

Manager

9. Year of construction:-

2004

10. Applicant's letter No:-ID No. 2024112217122 dated 26.11.24.

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	05 feet	N/A	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases				
	1. Upper floors	01 No.	02 No.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase	N/A	N/A	N/A	
	1. Upper floors	0.80 mtr.	0.93 mtr.	MR	
	2. Basements(not a part of guest house)	N/A	N/A	N/A	
	C. Protection of exits	N/A	N/A	N/A	
	1. Fire check door	Required	Provided	MR	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	N/A	N/A	N/A	
	2) Upper floors	12 a/c per hour	Exhaust fan	MR	
5.	Fire Extinguishers				
	1) Total numbers	12 Nos.	12 Nos.	MR	

	2) T-			
	2) Types	ABC & CO2	ABC & CO2	MR
5.	3) ISI marking	Required	Provided	MR
0.	First-Aid Hose Reel			
	Total number of each floor	01	01	MR
	2) Length of hose reel hose	30 m	30 m	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	DOSTORES IN THE SECURITY STATE	The state of the s	
	1) Type of detectors	Required	Provided	MR
	2) Location of main panel	Ground floor	Provided	MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Each floor	Provided	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
	1) Basement (not a part of guest house)	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants	T .		
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per floor	N/A	N/A	N/A
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
1	1) Ground level	N/A	N/A	N/A
	a) Discharge of main pump	N/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual stopping	N/A	N/A	N/A
	2) Terrace level		122222	
	a) Discharge of pump	180 LPM	180 LPM	MR
	b) Head of pump	30 mtr	30 mtr	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR

4.	Captive Water Storage for Fi	re Fighting		
	Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR
		Required	Provided	MR
15.	Exit Signage. Provision of Lifts.			
16.	a) Pressurization of lift	N/A	N/A	N/A
	shaft b) Pressurization of lift	N/A	N/A	N/A
	c) Communication in lift	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
		N/A	N/A	N/A
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Refuge Area Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System if any:	for Protection	on of special Risk,	NA

The above fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter No.F6/DFS/MS/GH/NDZ/2021/521 dated 10/12/21, under rule 35(6) of the Delhi Fire Service rules 2010. Accordingly, DFA is prepared and put up for kind perusal/approval please.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

10/12/24 Dycho(200

Mings m 200gs

Procto / Million

Hoger