

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001**



No. F6/DFS/MS/School/WZ/2024/ 1197

FIRE SAFETY CERTIFICATE

Certified that the Rose Public School, Located at RZ K2/423, Nihal Vihar, New Delhi-110041, comprised of Ground + 03 Upper Floors, owned/occupied by Rose Public School have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officer concerned of Fire Service on 03/12/2024 in the presence of Sh. Suresh Singh (Manager) and that the building/premises is fit for occupancy class " Educational Building" Group B with effect from 16 12 2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on_at New Delhi by.

Copy to:-

- 1. The Deputy Director, Delhi Municipal Corporation, Civic Centre, Minto Road, Delhi-110002.
- 2. The Principal, Rose Public School, RZ K2/423, Nihal Vihar, New Delhi-110041.

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form J (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name and address of the building: Rose Public School located at RZ K2/423, Nihal

2. Type of Occupancy Vihar, New Delhi-110041 : Educational

3. Type of Case : New

4. Details of previous NOC : Nil

5. Fire Safety directives Letter No. : NBC (Part-IV)

6. Date of inspection : 03/12/2024

7. Name of the Inspecting Officer : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side : Sh. Suresh Singh (Manager)

9. Year of Construction : 2018-19

10. Applicant's letter No. : email dated 21/10/2024
The building is comprised of ground + 03 upper floors only

| S No | Minimum standards on fire prevention and fire safety U/R 33 | NBC (Part-IV) Requirements | Provided at site | Remarks MR/NMR | |
|---------|-------------------------------------------------------------|-------------------------------|----------------------|-------------------|--|
| 1. | Access of building | | | | |
| | Road width | 06 m | Provided | MR | |
| | Gate width | 4.5 m | Provided | MR | |
| | Width of internal road | NA | NA | NA | |
| 2. | Number, width, Type & Arrangen | nents of exits | | | |
| | a. Number of staircases | | | | |
| | Upper floors | 02 | Provided | MR | |
| | Basements | NA | NA | NA | |
| | b. Width of staircases | | and the second | | |
| | Upper floors | | 5 m x 2 (01 iron mad | le) MR | |
| | Basements | NA | NA | NA | |
| | c. Protection of exits | 04 | | | |
| | Fire check door | NA | NA | NA | |
| | Pressurization | NA | NA . | NA | |
| | d. No of continuous staircase to terrace | 02 | Provided | MR | |
| | e. Width Of Corridor | 1.5 m | Provided | MR | |
| | f. Door Size | 1.2 m | Provided | MR | |
| 3. | Compartmentation | | NA | | |
| | Fire check door | NA | NA | NA | |
| | Sealing of electrical shafts | NA | NA | NA | |
| | Fire Rating of shaft door | NA | NA | NA | |
| | Water Curtain | NA | NA | NA | |
| | Fire Dampers | NA | NA | NA | |
| 4. | Smoke managements System | | | | |
| | Basements | NA | NA | NA | |
| | Upper floors | NA | NA | NA | |
| 5. | Fire Extinguishers | | | | |
| | Total numbers | 06 nos. | 10 nos. | MR | |
| | Types | ABC & CO ₂ | Provided | MR | |
| | ISI marking | ISI Marked | Provided | MR | |

| à | ۱, | ٠. |
|---|----|-----|
| | | ~ |
| 1 | | -1 |
| 1 | | - 1 |

| FI | rst – Aid Hose Reel | | | 1 |
|------|-------------------------------------------------------------|--------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | Total numbers on each floor | 01 | Provided | MR |
| | LenPgth of hose reel hose | 30 m | Provided | MR 🧳 |
| | Nozzle diameter | 05 mm | Provided | MR |
| A | automatic fire detection and alarming sy | | | |
| | Type of detectors | NA | NA | NA |
| | Location of Main Panel | NA | NA | NA |
| , | Location of Repeater Panel | NA | NA | NA |
| | Alternate source of power | NA | NA | NA |
| | Hooters' Location | NA | NA | NA |
| . 1 | MOEFA | NA | NA | NA |
| | Public Address System | NA | NA | NA |
| | Automatic Sprinkler System | | | |
| | Basements | NA | NA | NA |
| | Upper Floor | NA | NA | NA |
| | Sprinkler above false ceiling | NA | NA | NA |
| 1. | Internal Hydrants: | | N14 | NA |
| | Size of riser/down- comer | NA | NA NA | NA NA |
| | Number of hydrants per floor | NA | NA NA | NA NA |
| | Hose Box | NA | NA | INA |
| 12. | Yard Hydrants | DIA I | NA | NA |
| | Total number of hydrants | NA NA | NA NA | NA |
| 10 | Hose Box | INA | 13/1 | y |
| 13. | Pumping Arrangements: | | | |
| | Ground Level Discharge of main nump | NA | NA | NA |
| | Discharge of main pump Head of main pump | NA NA | NA | NA |
| | > Number of main pumps | NA | NA | NA |
| | > Jockey pump out put | NA | NA | NA |
| | > Jockey pump head | NA | NA | NA |
| | > Standby Pump out put | NA | NA · | NA |
| | > Standby Pump Head | NA | NA | NA |
| | ➤ Auto Staring/Manual stopping | NA | NA | NA |
| | ➤ Pump House Access | NA | NA | NA |
| | Terrace level | | | W. V. Salaci |
| | ➤ Discharge of pump | 450 lpm | Provided | MR |
| | > Head of the pump | 40 m | Provided | MR |
| | > Power supply | Required | Provided | MR |
| 1200 | > Auto starting of pump | Required | Provided | MR |
| 14. | | NIA | T NIA | NIA |
| | Under ground tank capacity | NA | NA NA | NA NA |
| | > Draw off connection | NA NA | NA NA | NA NA |
| | Fire service inletAccess to tank | NA NA | NA NA | NA NA |
| | Overhead Tank capacity | 10,000 ltrs. | NA Provided | NA MR |
| 15 | Exit Signage | Required | Provided | MR |
| 16. | | Required | Trovided | IVIK |
| . 0. | > Pressurization of Lift Shaft | NA | NA | NA |
| | > Pressurization of lift lobby | NA NA | NA NA | NA NA |
| | Communication in lift Car | NA NA | NA NA | NA NA |
| | ➤ Fireman's Grounding Switch | NA NA | NA NA | NA NA |
| | ➤ Lift Signage | NA NA | NA NA | NA NA |
| 12 | | | 1 | NA |
| 17. | | NA | NA | NA |
| 18. | Refuge Area | | | PERSONAL PROPERTY OF THE PERSONAL PROPERTY OF |
| | > Total area | NA | NA | NA |
| | ▶ Location | NA | | 1111 |

| MR | |
|----|---|
| MR | / |
| | |

| | | | 2/1/4 | | | |
|-----|--------------------------------------------------------------------------|----|-------|----|--|--|
| 19. | Fire control room | | | | | |
| | Detector system | NA | NA | NA | | |
| | panel | NA | NA | NA | | |
| | Flow Switch Panel | NA | NA | NA | | |
| | ➤ PA System Panel | NA | NA | NA | | |
| | Battery backupBuilding Floor Plans | NA | NA | NA | | |
| 20. | Special Fire Protection Systems for Protection of special Risks, if any; | NA | NA | NA | | |

Note:- The owner/occupier of the school building have submitted an affidavit that the school is located in non-confirming area and Abaadi kshetra & the drawing are not approved by MCD. The owner/occupier have submitted as built plan duly signed by registered Architect and owner of the school, which may be accepted

Fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view of substantial compliance of the minimum standards of fire prevention and fire safety requirements under the rules, grant of Fire safety Certificate is recommended under rule 35 of the Delhi Fire service Rules 2010 under the DFS Act-2007.

Accordingly DFA is prepared for approval & signature please.

Aman Kumar Lathar ADO (JWP)