

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110001**

No.F.6 DFS/MS/School/2024/SZ/1217

Dated: 23/12/2024

FIRE SAFETY CERTIFICATE

Certified that the M/s Swarn Public School, located at 171-A, Main Khirki Road, Malviya Nagar, New Delhi-110017 comprised of Basement, Ground plus Two upper floors (Basement not used for school purpose) owned / occupied by Swarn Public School was issued Fire Safety vide letter Certificate bv this department F6/DFS/MS/School/2021/SZ/1053 Dated 22/12/2021. The said premise was reinspected by officer concerned of this department on 17/12/2024 in presence of Ms. Amarjeet Kaur (Manager) and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education Circular No F.16//Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011 issued by Director of Education, Govt. of NCT of Delhi and the building is fit for occupancy class "Educational Building Group - B" with effect from 23/12/2024 for a period of Three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance, of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 23/12 2024 at New Delhi by

DIRECTOR Delhi fir E SERVICE

Copy to: -

1. Swarn Public School, at 171-A, Main Khirki Road, Malviya Nagar, New Delhi-17. 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-54.

Conditions for the validity of Fire Safety Certificate

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.

2. All the staff members must know the correct method of operation of firefighting

- 3. This certificate cannot be treated as regularization of unauthorized construction, if
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on

5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-

6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six





| | 1-1-7 | d | | | | |
|--------|--|--|-----------------------|-------------------|--|--|
| 1 | Name & Address of the Building | N KEPUKI | Cabani 171 A N | fain Khirk | | |
| fori | | Swarn Public School, 171-A, Main Khirk Road, Malviya Nagar, New Delhi-110017. | | | | |
| 2 | Type of Occupancy | Educational Building "Group-B" (School) | | | | |
| 3 | Building Comprised of | Basement, Ground + 02 Upper Floors (Basement not used for school purpose) | | | | |
| 4 | Type of Case | Denewal | | | | |
| 5 | Details of Previous NOC | F6/DFS/MS/School/2021/SZ/1053 Dated 22/12/2021 | | | | |
| 6 | Fire Safety Directives Letter No | DOE Circular Dated 01/03/2021 | | | | |
| 7 | Date of Inspection | 17/12/2024 | | | | |
| 8 | Name of the Inspecting Officers | Sh. Rajesh Kumar ADO (BCP) | | | | |
| 9 | Name & Designation of Officers | Ms. Amarjeet Kaur (Manager) | | | | |
| | from the building side | IVIS. Alliarject Rati (Manager) | | | | |
| 10 | Year of construction | 1997 | | | | |
| 11 | Applicant letter No. | Email dated 10/12/2024 | | | | |
| S. No. | | Old NOC | Provided at Site | Remarks | | |
| | and Fire Safety U/R 33 | Requirement | | MR/NMR | | |
| 1 | Access to Building. | Acqui ement | CARDINAL PRINT FOR | 11my 43 | | |
| | Road width | 06 mtr | Provided | MR | | |
| | Gate width | -NA- | 3.65 m & 3 m | -NA- | | |
| 1 | Width of internal road | -NA- | -NA- | -NA- | | |
| 2 | Number, width, type & arrangement of ex | 19196539 | | | | |
| - | a) Number of Staircase | its. | and the second second | | | |
| 4 | > Upper floors. | 02 Nos | 02 Nos | M/R | | |
| J- 5 | Basement floor. | -NA- | -NA- | -NA- | | |
| 11.0 | b) Width of Staircase | 1112 | 2000000 | | | |
| | > Upper floor | 1.50m /0.75m | 1.30m & 0.90m | M/R (old case) | | |
| 1 | ➤ Basement floor | -NA- | -NA- | -NA- | | |
| | c) Protection of exits | | | | | |
| | ➤ Fire check door | -NA- | -NA- | -NA- | | |
| | ➤ Pressurization | -NA- | -NA- | -NA- | | |
| | d) No. of continuous staircase to terrace | Required | 02 Nos | MR | | |
| 1 | e) Width of corridor | -NA- | -NA- | -NA- | | |
| 1 | f) Door size | 1.0 mtr | Provided | MR | | |
| 3 | Compartmentation. | NA | 70 N N N | T | | |
| - | Fire check door. Seeling of electrical shorts. | -NA- | -NA- | -NA- | | |
| | Sealing of electrical shafts. Fire rating of shaft door. | -NA- | -NA- | -NA- | | |
| | Water curtain | -NA- | -NA- | -NA- | | |
| | Fire dampers. | -NA- | -NA- | -NA- | | |
| 4 | | lielo | -11/14 | -NA- | | |
| - | Basement | 30 ACPH | NA | NIA | | |
| | Upper floors | 12 ACPH | -NA- | NA -NA- | | |
| 5 | | | The West and Section | -IVA- | | |
| | Total numbers | ISI mark | 15 No's | MR | | |
| | Types | | ABC & CO2 | MR | | |
| | ISI Marking | | Provided | MR | | |
| 6 | First Aid Hose Reels. | 3 | The figure | AVALL | | |
| | Total numbers on each floor. | | 01 No | M/R | | |
| | Length of hose-reel hose. | Hose reel | 30m | M/R | | |
| | Nozzle Diameter | 1 | 5mm | M/R | | |
| 7 | Automatic fire detection & alarming system. | | | | | |
| | Type of detectors | -NA- | -NA- | -NA- | | |

| ang | Ha Thomas |
|---|-----------|
| NA | -NA- |
| -NA- | MR |
| Provided | -NA- |
| -NA- | -NA- |
| La | |
| 100 mm | MR |
| 01 | -NA- |
| 01 | -NA- |
| | 1 314 |
| -NA- | -NA- |
| -NA- | -NA- |
| 1111(4)44 | |
| NA | -NA- |
| -NA- | |
| -NA- | -NA- |
| di ana d | MR |
| Provided | |
| Provided | MR |
| Provided | MR |
| provided | MR |
| -NA- | -NA- |
| | -NA- |
| -NA- | -NA- |
| -NA- | -NA- |
| -NA- | MR |
| Provided | MR |
| Provided | IVIK |
| -NA- | -NA- |
| | -NA- |
| -NA- | |
| -NA- | -NA- |
| NIA | TATA |
| -NA- | -NA- |
| -NA- | -NA- |
| | |

| | Location of Main Panel | NI A | -NA- | -NA- |
|------|---|---------------|----------------------|---------|
| | Location of Repeater Panel | -NA- | -NA- | -NA- |
| | Alternate source of power | -NA- | | -NA |
| | Hooter's location | -NA- | -NA- | -NA- |
| 8 | MOEFA Slocation | -NA- | -NA- | MR |
| 9 | | Required | Provided | -NA- |
| 10 | Public Address System | -NA- | -NA- | -NA- |
| 10 | Automatic Sprinkler System | | | -NA- |
| | Basement | -NA- | -NA- | -NA- |
| | Upper floors | -NA- | -NA- | -NA- |
| | Sprinkler above false ceiling | -NA- | -NA- | -NA- |
| 11 | Internal Hydrants. | 4 | | MR |
| | Size of Riser/Down-comer | Required | 100 mm | -NA- |
| | Number of Hydrant per floor | -NA- | 01 | |
| | Hose box. | -NA- | 01 | -NA- |
| 12 | Yard Hydrants. | | 2000 | -NA- |
| el u | Total number of hydrants. | -NA- | -NA- | |
| | Hose box. | -NA- | -NA- | -NA- |
| 13 | Pumping arrangements. | | 1111/11/11 | |
| | Ground Level | | | -NA- |
| | Discharge of main pump. | -NA- | -NA- | -NA- |
| | Head of main pump. | -NA- | -NA- | -NA- |
| | | -NA- | -NA- | -NA- |
| | Participation of the Control of the | -NA- | -NA- | -NA- |
| | > Jockey Pump output. | -NA- | -NA- | -NA- |
| | Jockey Pump head. | -NA- | -NA- | -NA- |
| | Standby Pump output. | -NA- | -NA- | |
| | Standby Pump head. Auto Starting/Manual Stopping. | -NA- | -NA- | -NA- |
| | Terrace Level | | Described. | MR |
| | Discharge of pump. | 450 LPM | Provided Provided | MR |
| | > Head of pump. | 40 m | Provided | MR |
| | Power supply. | Required | provided | MR |
| | > Auto starting of pump. | Required | provided | 1,124 |
| 14 | Captive water storage for fire fighting. | | -NA- | -NA- |
| 14 | Inderground tank capacity. | -NA- | -NA- | -NA- |
| | > Draw-off connection. | -NA- | -NA- | -NA- |
| | Fire Service Inlet. | -NA- | -NA- | -NA- |
| | > Access to tank. | -NA- | Provided | MR |
| | Overhead tank capacity. | 10,000 Ltrs | Provided | MR |
| 15 | Exit Signage. | Required | Tiovidea | ,,,,,,, |
| _ | Provision of Lifts. | N/A I | -NA- | -NA- |
| 16 | • Pressurization of lift shaft. | -NA- | -NA- | -NA- |
| | Pressurization of lift lobby. | -NA- | -NA- | -NA- |
| | Communication in lift car. | -NA- | -NA- | -NA- |
| | Fireman's switch. | -NA- | | _ |
| | Lift signage. | -NA- | -NA- | -NA- |
| 17 | Standby Power Supply | -NA- | -NA- | -NA- |
| 18 | Refuge Area | | | 4 |
| .0 | Total area | -NA- | -NA- | -NA- |
| | Location | -NA- | -NA- | -NA- |
| • | Fire Control Room. | - K 194 1 | | - |
| 9. | D | -NA- | -NA- | -NA- |
| | to personal religions of | -NA- | -NA- | |
| | Flow switch panel. | CONTROL STATE | N/A | -NA- |



| No. | PA system panel. Battery backup. | -NA- -NA- | -NA- | -NA- |
|-----|--|--------------|------|------|
| | | | | -NA- |
| | | | | |
| | Building floor plan. | -NA- | -NA- | -NA- |
| 20. | Special Fire Protection System for the | -NA- 1 | | -NA- |

The fire protection system provided in the building / premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the fire safety certificate issued vide letter No. F6/DFS/MS/School/2021/SZ/1053 Dated 22/12/2021, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

Approved, F-1- Letter in pulity
your synature of