

FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/SZ/2024 8NOT 15

Dated: 27/02/2024

FIRE SAFETY CERTIFICATE

Certified that the. Shri Govindam Hall (A Unit of Gokul garden Banquets Pvt. Ltd) Located at 3rd Floor, WZ 306 – O, Khasra No. 72/6/1, Data Ram Marg, Chotiyal Palam Village, New Delhi – 110045 in a building comprised of Basement + Ground + 3 Upper Floors owned/ occupied by Gokul garden Banquets Pvt. Ltd have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officer concerned of this department on 10/02/2024 in the presence of Sh. Rajeev Solanki (Director) and found that the said building that the premises is fit for occupancy class "Assembly" Group D (At 3rd Floor only) with effect from 27/02/2024 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .27. 92. 20.24... at New Delhi by.

Adul Garg

Delhi Fire Service

Copy to:

1. The Joint Commissioner Police, Licensing, 1st Floor, PS, Defence Colony, N Delhi.

2. Sh. Rajeev Solanki (Director) Shri Govindam Hall (A Unit of Gokul garden Banquets Pvt. Ltd) Located at 3rd Floor, WZ 306 - O, Khasra No. 72/6/1, Data Ram Marg, Chotiyal Palam Village, New Delhi - 110045.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used strictly as per building bye laws
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

 Name & address of the building: Shri Govindam Hall (A Unit of Gokul garden Banquets Pvt. Ltd) Located at 3rd Floor, WZ 306 - O, Khasra No. 72/6/1, Data Ram Marg, Chotiyal Palam Village, New Delhi - 110045

2. Type of Occupancy

: Assembly (At 3rd Floor) in a building comprised of Basement

+ Ground + 3 Upper Floors

3. Type of Case

:New

4. Details of previous NOC

: Nil

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

: 10/02/2024

7. Name of the Inspecting Officer: ADO (DWK)

8. Name and designation of Officer

from the building side

: Sh. Rajeev Solanki (Director)

9. Year of Construction

 Applicant's letter No. : Email dated 29/01/2024 & online application No. 2023120719315, dated 12/12/2023

| Fire Dampers NA Provided NA Provided Total numbers Total numbers Types NA Provided Provided Provided Provided Required Provided NA | NBC Requirement Provided at site | | | | | |
|--|----------------------------------|----------|--|--|--|--|
| Gate width Width of internal road 2. Number, width, Type & Arrangements of exits a. Number of staircases Upper floors Basements Width of staircases Upper floors Basements Width of staircases Upper floors Basements C. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 3. Compartmentation Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke managements System Basements Upper floors Required NA | | | | | | |
| Width of internal road 2. Number, width, Type & Arrangements of exits a. Number of staircases • Upper floors Basements b. Width of staircases • Upper floors Basements c. Protection of exits • Fire check door • Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 3. Compartmentation • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door water Curtain • Fire Dampers 4. Smoke managements System • Basements • Upper floors • Total numbers • Total numbers • Total numbers • Types Arrangements of exits NA Provided Provided Provided NA | | MR | | | | |
| 2. Number, width, Type & Arrangements of exits a. Number of staircases • Upper floors • Basements b. Width of staircases • Upper floors • Basements c. Protection of exits • Fire check door • Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 3. Compartmentation • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers 4. Smoke managements System • Basements • Upper floors • Total numbers • Total numbers • Types • ABC & CO2 2 2 2 2 2 2 2 4 NA Provided Provided NA NA NA NA NA NA NA NA NA N | NA | | | | | |
| a. Number of staircases Upper floors Basements Upper floors Upper floors Upper floors Basements Upper floors Basements C. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace E. Width Of Corridor f. Door Size 3. Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke managements System Basements Upper floors Basements Basements Base | | | | | | |
| a. Number of staircases Upper floors Basements Upper floors Upper floors Upper floors Basements Upper floors Basements C. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace E. Width Of Corridor f. Door Size 3. Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke managements System Basements Upper floors Basements Basements Base | | | | | | |
| Basements b. Width of staircases Upper floors Basements C. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace E. Width Of Corridor F. Door Size Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Basements Upper floors Basements NA Required Provided NA | | | | | | |
| b. Width of staircases Upper floors Basements Fire check door Pressurization A No of continuous staircase to terrace E Width Of Corridor F Door Size Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers A Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Types Do 2 Provided Provided Provided NA N | 2 | | | | | |
| Upper floors Basements C. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 3. Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Total numbers Types Sealing of exits Required Provided NA N | Provided | | | | | |
| Basements C. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 3. Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Total numbers Total numbers Types NA Required Provided Provided NA | TAX TAX | | | | | |
| c. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 3. Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke managements System Basements Upper floors Total numbers | .17m | MR NA | | | | |
| Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 3. Compartmentation | led | | | | | |
| Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 3. Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke managements System Basements Upper floors Total numbers Total numbers Types NA | | 1.32.8 | | | | |
| Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 3. Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke managements System Basements Upper floors Total numbers Total numbers Types NA Required NA NA NA NA NA NA NA NA NA N | Provided | | | | | |
| staircase to terrace e. Width Of Corridor f. Door Size 2m,1.5m Provided 3. Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Types NA NA NA NA NA NA NA NA NA N | | | | | | |
| e. Width Of Corridor f. Door Size 2m,1.5m Provided 3. Compartmentation Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 4. Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Types NA | | NA MR | | | | |
| f. Door Size 2m,1.5m Provided 3. Compartmentation • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers 4. Smoke managements System • Basements • Upper floors • Total numbers • Types • Types 2m,1.5m NA NA NA NA NA NA NA NA NA N | NA | | | | | |
| 3. Compartmentation • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers 4. Smoke managements System • Basements • Upper floors • Total numbers • Types • Types • Types • Fire check door NA | | | | | | |
| Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Basements Upper floors Total numbers Types Sealing of electrical shafts NA N | | MR | | | | |
| Fire Rating of shaft door Water Curtain Fire Dampers NA Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Total numbers Types Types ABC & CO2 | N/ | | | | | |
| Water Curtain Fire Dampers NA | | A NA | | | | |
| Water Curtain Fire Dampers NA Provided Dupper floors Total numbers Total numbers Types Types NA Provided Provided Provided Provided Provided Required Provided Provided Required Total numbers Total numbers Types Types | NA NA NA | | | | | |
| 4. Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Types NA Provided Provided Provided Provided Provided Provided Provided Provided | | | | | | |
| 4. Smoke managements System | | | | | | |
| Upper floors Required Provided Total numbers Types ABC & CO2 | | NA | | | | |
| 5. Fire Extinguishers Total numbers Types Types Types Required Provided Provided Provided Provided Provided Provided | | NA | | | | |
| Total numbers Types | | | | | | |
| Types ABC & CO2 Pr ABC & CO2 Pr Pr Pr Pr Pr Pr Pr Pr Pr P | | MR | | | | |
| Types ABC & CO2 | rovided | 1.00 | | | | |
| | rovided | MR | | | | |
| ISI marked | rovided | MR | | | | |
| 6. First – Aid Hose Reels | tovided | MR | | | | |

| | Total numbers on ea | | | | Provided | | MR | |
|-----|---|------------------------------|-----------|--------------------------------|----------|----------|----------|--|
| | floor | 30 m | | Provided | | MR MR | | |
| | Length of hose reel h | nose 5 | nose 5 mm | | Provided | | IVIK | |
| | Nozzle diameter | | | | | | | |
| | Automatic fire detection and | | | m Provide | | IN | ИR | |
| | Type of detectors | | 1100 | | | 2.5 | /IR | |
| | Location of Main | Require | | Provided | | | /IR | |
| | Panel | Required Required | | Provided Provided | | MR MR | | |
| | Location of Repeater | | | | | | | |
| | Panel | Require | ed | Provided | | 1,4 | 110 | |
| | Alternate source of | | | | | | | |
| | power | | | | | | | |
| | Hooters' Location | | | | | N | 1R | |
| 8. | MOEFA | Require | Required | | Provided | | MR | |
| 9. | Public Address System | blic Address System Required | | Provided | | | 1122 | |
| 10. | Automatic Sprinkler System | | | 1 5 11.4 | | N | A | |
| 10. | Basements | NA | | Provided | | N | | |
| | Upper Floor | NA | | NA NA | | N | | |
| | Sprinkler above | NA | | NA | | | | |
| | false ceiling | | | | T | | | |
| 11. | Internal Hydrants | | | Provided | | M | | |
| 11. | Size of riser/down- | 150 mm | 1 | Provided | | M | | |
| | comer | 2 | | Provided | | M | R | |
| | Number of hydrants | 2 | | Tiovided | | | | |
| | per floor | | | | | | | |
| | Hose Box | | | | | | | |
| 12. | Yard Hydrants | NIA | | NA | | N/ | | |
| | Total number of | NA NA | | NA | _ | N/ | A | |
| | hydrants | INA | | 100110000 | | | | |
| | Hose Box | | | | | _ | - | |
| 13. | Pumping Arrangements | T | | | | T N | íR. | |
| | Ground Level | 2280lpm | 1 | Provided | | _ | IR IR | |
| | Discharge of main | 70m | === | Provided | | | IR IR | |
| | pump Head of main pump | 1 | | Provided | | | IR IR | |
| | > Head of main pump | 180lpm | | Provided | | | 1R | |
| | numns | 70m | | Provided | | - | IR. | |
| | > lockey pump out put | 2280lpm | 1 | Provided | | - | IR | |
| | Jockey pump head | NA | | Provided | | | íR | |
| | Standby Pump out | Required | 1 | Provided | | 1.4 | 7.7 | |
| | put | | | Provided | | M | ſR | |
| | Standby Pump Head | Required | 1 | Provided | | | | |
| | Auto Staring/Manual | 0001 | | Provided | | I | MR | |
| | stopping | 900 lpm | | Provided | | | MR | |
| | > Pump House Access | 40 m | | Provided | | | MR | |
| | Terrace level Discharge of nump | Required | | Provided | | | MR | |
| | Discharge of pump | Required | | Flovided | | 0.7 | | |
| | Head of the pumpPower supply | | | 111 | | | | |
| | > Power supply > Auto starting of | | | 1 | | | | |
| | 1 | | | والمراج والمراج | | | | |
| 14 | pump Captive water Storage for fire | fighting | | | | | 1.0 | |
| 14. | Under ground tank | 150000 L | , F | Provided | | | MR | |
| | capacity | Required | | rovided | | | MR | |
| | > Draw of connection | Required | _ | rovided | | | MR | |
| | Fire service inlet | Required | - | rovided | | | MR | |
| | > Access to tank | 10,000 ltr | - | 0000 ltr | | | MR | |
| | Overhead Tank | , | | and the second College College | | | | |
| | capacity | | | | | | | |
| - | Exit Signage | Required | P | rovided | | | MR | |
| _ | Provision of Lifts | | | | | | | |
| 6. | ► Pressurization of Lift S | haft 1 | NA | | NA | | NA | |
| | / I TESSUITZULION OF EAR O | - | P. | | 15 15 15 | | | |

| | Pressurization of lift l | Pressurization of lift lobby Communication in lift Car Re | | | NA | | NA | |
|------------|--|---|------------------|----------------------|------------|------|----------|--|
| | Communication in lif | | | Required Provi | | | MR | |
| | Fireman's Grounding | Switch | Required Provide | | | | | |
| | Lift Signage | | Required Provid | | ded | MR | | |
| 17 | Standby power supply | Require | | Provid | led | | MR | |
| 17. 18. | Refuge Area NA | | NA . | | | 120 | | |
| | > Total area | NA | | NA | | 1700 | NA | |
| | Location | NA NA | | N/ | | Α | | |
| 19. | Fire control room | | | | | | | |
| | Detector system panel Flow Switch Panel | NA | | NA | | _ | NA NA | |
| | | NA NA NA | | NA NA NA NA | | | NA NA | |
| | | | | | | | | |
| | > PA System Panel | | | | | | NA | |
| | Battery backup | | | | | | NA | |
| | ➤ Building Floor Plans | - Con | NA | | NA | NA | | |
| 20. | Special Fire Protection Syster Protection of special Risks, i | ns for f any; | INA | | \$15.5 | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under Rule 35 of the Delhi Fire Service Rules 2010.

- Shri Govindam Hall (A Unit of Gokul garden Banquets Pvt. Ltd) Located at 3rd Floor, WZ
 Khasra No. 72/6/1, Data Ram Marg, Chotiyal Palam Village, New Delhi 110045.
- 2. As per plan submitted by the applicant the area of the Shri Govindam hall is 127.73 m²
- 3. As per part IV, NBC-2016, table no 4.3 under clause 4.4.2.1 the occupant load for dining area and restaurant is 1.8. Accordingly the number of seats come out to be 71 (127.73 /1.8=71) for whole Shri Govindam hall.

The total seating capacity comes out be 71

Sign. of the Inspecting Officer

Name Ulay Ur Simy,

Designation Atolowy

Senecter / 1/2/24

oir of letter is histop for som

DIRECTOR / MINA

N201